



5 **IHE Quality, Research and Public Health
Technical Framework Supplement**

10 **Retrieve Process for Execution
(RPE)**

15 **Trial Implementation**

20 Date: October 27, 2015
Author: QRPH Technical Committee
Email: qrph@ihe.net

25 **Please verify you have the most recent version of this document. See [here](#) for Trial Implementation and Final Text versions and [here](#) for Public Comment versions.**

Foreword

30 This is a supplement to the IHE Quality, Research and Public Health (QRPH) Technical Framework 0.1. Each supplement undergoes a process of public comment and trial implementation before being incorporated into the volumes of the Technical Frameworks.

This supplement is published on October 27, 2015 for trial implementation and may be available for testing at subsequent IHE Connectathons. The supplement may be amended based on the
35 results of testing. Following successful testing it will be incorporated into the Quality, Research and Public Health Technical Framework. Comments are invited and may be submitted at http://www.ihe.net/QRPH_Public_Comments. This supplement describes changes to the existing technical framework documents.

“Boxed” instructions like the sample below indicate to the Volume Editor how to integrate the
40 relevant section(s) into the relevant Technical Framework volume.

<i>Amend Section X.X by the following:</i>
--

Where the amendment adds text, make the added text **bold underline**. Where the amendment removes text, make the removed text **~~bold strikethrough~~**. When entire new sections are added, introduce with editor’s instructions to “add new text” or similar, which for readability are not
45 bolded or underlined.

General information about IHE can be found at: www.ihe.net.

Information about the IHE QRPH domain can be found at: http://www.ihe.net/IHE_Domains.

Information about the organization of IHE Technical Frameworks and Supplements and the
50 process used to create them can be found at: http://www.ihe.net/IHE_Process and <http://www.ihe.net/Profiles>.

The current version of the IHE QRPH Technical Framework can be found at:
http://www.ihe.net/Technical_Frameworks.

55

CONTENTS

	Introduction.....	6
	Open Issues and Questions	6
60	Closed Issues	6
	Volume 1 – Integration Profiles.....	7
	1.n Copyright Permissions	7
	2.5 Dependencies of the RPE Integration Profile	7
	2.7 History of Annual Changes	7
65	X Retrieve Process for Execution (RPE) Profile	8
	X.1 RPE Actors/Transactions	8
	X.1.1 Actor Descriptions and Requirements.....	9
	X.1.1.1 Process Definition Manager	9
	X.1.1.2 Process State Manager.....	9
70	X.1.1.3 Process Activity Executor	10
	X.2 RPE Actor Options.....	11
	X.2.1 Retrieve Process Definitions Option	12
	X.2.2 Retrieve Activities Option.....	12
	X.2.3 Update Activity Option	12
75	X.3 Groupings.....	12
	X.4 RPE Process Flow	12
	X.4.1 Use Cases	12
	X.4.2 Process Flow.....	14
	X.5 RPE Security Considerations	16
80	X.5.1 Recommendations	17
	X.6 RPE Version mapping.....	18
	Appendix A: Actor Summary Definitions	19
	Appendix B: Transaction Summary Definitions.....	20
	Glossary	21
85	Volume 2 - Transactions.....	22
	3 IHE Transactions	22
	3.Y1 Retrieve Process Definitions	22
	3.Y1.1 Scope	22
	3.Y1.2 Use Case Roles.....	22
90	3.Y1.3 Referenced Standards	23
	3.Y1.4 Interaction Diagram.....	23
	3.Y1.4.1 Retrieve Process Definitions Message	24
	3.Y1.4.1.1 Trigger Events.....	24
	3.Y1.4.1.2 Message Semantics	24
95	3.Y1.4.1.3 Expected Actions	25
	3.Y1.4.2 Retrieve Process Definitions Response Message	25
	3.Y1.4.2.1 Trigger Events.....	25
	3.Y1.4.2.2 Message Semantics	25

	3.Y1.4.2.3 Expected Actions	26
100	3.Y1.5 Security Considerations.....	26
	3.Y1.6 Protocol Requirements	26
	3.Y1.6.1 Sample SOAP Messages	27
	3.Y1.6.1.1 Sample Retrieve Process Definitions SOAP Request.....	27
	3.Y1.6.1.2 Sample Retrieve Process Definitions SOAP Response	27
105	3.Y2 Initiate Process	29
	3.Y2.1 Scope	29
	3.Y2.2 Use Case Roles	29
	3.Y2.3 Referenced Standards	29
	3.Y2.4 Interaction Diagram.....	30
110	3.Y2.4.1 Initiate Process Message.....	30
	3.Y2.4.1.1 Trigger Events.....	30
	3.Y2.4.1.2 Message Semantics	30
	3.Y2.4.1.3 Expected Actions	31
	3.Y2.4.2 Initiate Process Response Message	31
115	3.Y2.4.2.1 Trigger Events.....	31
	3.Y2.4.2.2 Message Semantics	31
	3.Y2.4.2.3 Expected Actions	32
	3.Y2.5 Security Considerations.....	32
	3.Y2.6 Protocol Requirements	32
120	3.Y2.6.1 Sample SOAP Messages	33
	3.Y2.6.1.1 Sample Initiate Process SOAP Request.....	33
	3.Y2.6.1.2 Sample Initiate Process SOAP Response	34
	3.Y3 Retrieve Activities.....	34
	3.Y3.1 Scope	34
125	3.Y3.2 Use Case Roles.....	34
	3.Y3.3 Referenced Standards	34
	3.Y3.4 Interaction Diagram.....	35
	3.Y3.4.1 Retrieve Activities Message	35
	3.Y3.4.1.1 Trigger Events.....	35
130	3.Y3.4.1.2 Message Semantics	35
	3.Y3.4.1.3 Expected Actions	35
	3.Y3.4.2 Retrieve Activities Response Message.....	36
	3.Y3.4.2.1 Trigger Events.....	36
	3.Y3.4.2.2 Message Semantics	36
135	3.Y3.4.2.3 Expected Actions	36
	3.Y3.5 Security Considerations.....	37
	3.Y3.6 Protocol Requirements	37
	3.Y3.6.1 Sample SOAP Messages	37
	3.Y3.6.1.1 Sample Retrieve Activities SOAP Request	38
140	3.Y3.6.1.2 Sample Retrieve Activities SOAP Response.....	38
	3.Y4 Update Activity	39
	3.Y4.1 Scope	39

	3.Y4.2 Use Case Roles	39
	3.Y4.3 Referenced Standards	39
145	3.Y4.4 Interaction Diagram.....	40
	3.Y4.4.1 Update Activity Message.....	40
	3.Y4.4.1.1 Trigger Events.....	40
	3.Y4.4.1.2 Message Semantics	40
	3.Y4.4.1.3 Expected Actions	41
150	3.Y4.4.2 Update Activity Response Message	41
	3.Y4.4.2.1 Trigger Events.....	41
	3.Y4.4.2.2 Message Semantics	42
	3.Y4.4.2.3 Expected Actions	42
	3.Y4.5 Security Considerations.....	42
155	3.Y4.6 Protocol Requirements	42
	3.Y4.6.1 Sample SOAP Messages	43
	3.Y4.6.1.1 Sample Update Activity SOAP Request.....	43
	3.Y4.6.1.2 Sample Update Activity SOAP Response	44
	3.Y5 Send Process State Alert	44
160	3.Y5.1 Scope	44
	3.Y5.2 Use Case Roles	45
	3.Y5.3 Referenced Standards	45
	3.Y5.4 Interaction Diagram.....	45
	3.Y5.4.1 Send Process State Alert Message.....	46
165	3.Y5.4.1.1 Trigger Events.....	46
	3.Y5.4.1.2 Message Semantics	46
	3.Y5.4.1.3 Expected Actions	47
	3.Y5.4.2 Send Process State Alert Response Message	47
	3.Y5.4.2.1 Trigger Events.....	47
170	3.Y5.4.2.2 Message Semantics	47
	3.Y5.4.2.3 Expected Actions	47
	3.Y5.5 Security Considerations.....	47
	3.Y5.6 Protocol Requirements	47
	3.Y5.6.1 Sample SOAP Messages	48
175	3.Y5.6.1.1 Sample Send Process State Alert SOAP Request.....	48
	3.Y5.6.1.2 Sample Send Process State Alert SOAP Response	49

Introduction

180 Retrieve Process for Execution (RPE) is a proposed IHE profile for *collaborative workflow* or *collaborative process management* involving three main actors:

1. the manager of process definitions
2. the manager of runtime processes
3. the performer of process activities

185 Note that the process definition contains specification for all activities to be performed. An activity defines a specific act, several of which define the entire process.

RPE started as Retrieve *Protocol* for Execution Profile, a proposed automated mechanism for an Electronic Health Record (EHR) to retrieve a complex set of clinical research instructions (a study protocol) from a research sponsor's Electronic Data Capture (EDC) system or research
190 site's Clinical Trials Management System (CTMS) and to execute these instructions within the EHR. Interest has since grown to expand RPE to support processes from other domains involving collaborative workflows like quality, public health and patient care support. RPE now does this consistent with accepted IT standards for process management. In September of 2011, RPE underwent a substantial re-write that required current users of RPE to re-develop their
195 implementations of the profile. The current version harmonizes the original Retrieve *Protocol* for Execution and the new Retrieve *Process* for Execution to lessen the burden on users of the profile to conform to the profile.

RPE defines the transport mechanism for process definitions, but does not provide the definitions per se. Additional profiles that define specific processes will complement RPE and bring the
200 process automation capability to completion. One of these profiles is the Clinical Research Process Content (CRPC) Profile.

Open Issues and Questions

No open issues at this time.

Closed Issues

205 No closed issues at this time.

Volume 1 – Integration Profiles

Add the following to Section 1.1.5

210

1.n Copyright Permissions

To be completed

Add the following to Section 2.5

215

2.5 Dependencies of the RPE Integration Profile

Retrieve Process for Execution (RPE) is not strictly dependent on any IHE profile but, for performance of activities, the Retrieve Form for Data-capture (RFD) and Redaction Services Profiles can be used very synergistically for form-based submission of appropriately-redacted EHR data.

220

Add the following to Section 2.7

2.7 History of Annual Changes

225 *To be completed*

Add Section X to the QRPH Technical Framework

X Retrieve Process for Execution (RPE) Profile

230 Retrieve Process for Execution (RPE) is a proposed IHE profile for *collaborative workflow* or *collaborative process management* involving three main actors:

1. the manager of process definitions
2. the manager of runtime processes
3. the performer of process activities

X.1 RPE Actors/Transactions

235 Figure X.1-1 shows the actors directly involved in the Retrieve Process for Execution Integration Profile and the relevant transactions between them. Other actors that may be indirectly involved due to their participation in other profiles are not necessarily shown.




Figure X.1-1: RPE Actor Diagram

240

Table X.1-1 lists the transactions for each actor directly involved in the RPE Profile. In order to claim support of this integration profile, an implementation must perform the required transactions (labeled “R”). Transactions labeled “O” are optional. A complete list of options defined by this integration profile, which implementations may choose to support, is listed in Section X.2.

245

Table X.1-1: RPE Actors and Transactions

Actors	Transactions	Optionality	Section in Vol. 2
Process Definition Manager	Retrieve Process Definitions [QRPH-20]	R	QRPH TF-2:3.Y1
Process State Manager	Retrieve Process Definitions [QRPH-20]	O	QRPH TF-2:3.Y1
	Initiate Process [QRPH-25]	R	QRPH TF-2:3.Y2
	Retrieve Activities [QRPH-26]	O	QRPH TF-2:3.Y3
	Update Activity [QRPH-27]	O	QRPH TF-2:3.Y4
	Send Process State Alert [QRPH-28]	R	QRPH TF-2:3.Y5
Process Activity Executor	Retrieve Process Definitions [QRPH-20]	R	QRPH TF-2:3.Y1
	Initiate Process [QRPH-25]	R	QRPH TF-2:3.Y2
	Retrieve Activities [QRPH-26]	O	QRPH TF-2:3.Y3
	Update Activity [QRPH-27]	O	QRPH TF-2:3.Y4
	Send Process State Alert [QRPH-28]	R	QRPH TF-2:3.Y5

X.1.1 Actor Descriptions and Requirements

X.1.1.1 Process Definition Manager

250 The Process Definition Manager manages access to a repository of process definitions, allowing for search and retrieval.

An example would be a research sponsor providing access to the clinical research protocols it has developed. Another would be a provider of evidence-based clinical practice guidelines.


X.1.1.2 Process State Manager

255 The Process State Manager manages the initiation and state of runtime process instances. The Process State Manager typically also supports the initiation and lifecycle management of task activities associated with a process while providing the ability for task performers to retrieve and update activities.

260 An example would be a research sponsor conducting clinical trials in conjunction with its EHR participants. Another would be an EHR performing clinical care in accordance with executable guideline-based processes.

The states of a process from the perspective of RPE actors¹ are indicated below:

¹ A BPMN 2.0 process and its activities may undergo more complex state transitions as per the BPMN 2.0 specification, Section 13.2.2, but these are the ones of interest to the Process Activity Executor. (Note the “Exited” state is any non-normal end state reached by a process or activity.)



265 All state transitions above are managed by the Process State Manager which can then use the Send Process State Alert transaction to notify the Process Activity Executor.


X.1.1.3 Process Activity Executor

270 The Process Activity Executor performs activities as prescribed by a running process being managed by a Process State Manager. The Process Activity Executor retrieves current activity or task lists, works its list, updating the Process State Manager on activity state until completion. This cycle is repeated until all process activities have been worked and the process itself completes.

275 An example would be an EHR performing activities as part of a clinical trial being managed by a research sponsor. Another example would be an EHR performing guideline-based care process activities.

The states of an activity from the perspective of RPE actors² are indicated below:

² A BPMN 2.0 activity may undergo more complex state transitions as per the BPMN 2.0 specification, Section 13.2.2, but these ones are of interest to the Process Activity Executor. (Note the “Exited” state is any non-normal end state reached by an activity.)



280 The Process State Manager is responsible for transitioning the activity into the “Active” state and possibly forcing it into a non-normal end state, i.e., “Exited” and using the Send Process State Alert transaction to notify the Process Activity Executor.

The Process Activity Executor is responsible for marking the activity “Completed” and using the Update Activity transaction to update the Process State Manager with this change as well as any associated output data.

285 **X.2 RPE Actor Options**

Table X.2-1: RPE Actor Options

Actor	Options	Vol & Section
Process State Manager	Retrieve Process Definitions [QRPH-20]	QRPH TF-2:3.Y1
Process State Manager	Retrieve Activities [QRPH-26]	QRPH TF-2:3.Y3
Process State Manager	Update Activity [QRPH-27]	QRPH TF-2:3.Y4
Process Activity Executor	Retrieve Activities [QRPH-26]	QRPH TF-2:3.Y3
Process Activity Executor	Update Activity [QRPH-27]	QRPH TF-2:3.Y4

The optional transactions extend the capabilities of the participating actor. Each actor can participate in any or all appropriate optional transactions.

290 **X.2.1 Retrieve Process Definitions Option**

The Retrieve Process Definitions Option allows a Process State Manager to retrieve the process definition. A Process State Manager that supports the Retrieve Process Definitions Option shall support the QRPH-20 transaction.

X.2.2 Retrieve Activities Option

295 The Retrieve Activities Option allows a Process State Manager or a Process Activity Executor to retrieve the current set of activities it needs to execute as part of processes it is a participant in and managed by the given Process State Manager. A Process State Manager or Process Activity Executor that supports the Retrieve Activities Option shall support the QRPH-26 transaction."

X.2.3 Update Activity Option

300 Update Activity allows a Process Activity Executor to provide an update on activity's state or data to a Process State Manager for a process it is a participant in. A Process Activity Executor that supports the Update Activity Option shall support the QRPH-27 transaction.

X.3 Groupings

No groupings specified.

305 **X.4 RPE Process Flow**

X.4.1 Use Cases

The clinical research use case below describes the before and after effects of implementing the Retrieve Process for Execution (RPE) Profile for an investigational new drug clinical trial scenario.

310 • Scenario

The setting for the clinical trial use case is a physicians' practice where patient care is delivered side-by-side with clinical research. The site, Fictitious Medical Group, is a multi-site physician practice, employing over 100 physicians in a variety of specialties. The Fictitious CEO encourages the physicians to participate as site investigators for pharmaceutical-sponsored clinical trials.

315

Before RPE

Preconditions

1. A Clinical Research Protocol is defined by a clinical trials expert at Sponsor, a biopharma research company.

- 320
2. Fictitious provides support for clinical research activities in the form of a Research Department of twelve dedicated study coordinators, mostly RNs, along with clerical and data-entry support personnel.
 3. Fictitious Medical Group uses an Electronic Health Record (EHR) and a number of sponsor-provided Electronic Data Capture (EDC) systems for documenting clinical trial activities.
- 325

Clinical Research Site's Involvement:

330 Fictitious involvement in a clinical study begins when the Research Department receives a request for proposal (RFP) from Sponsor. A Study Coordinator, Patricia Zone, RN, evaluates the RFP for business viability and clinical appropriateness, provides the requested documentation back to the sponsor, and agrees to participate. After being approved as a site for the Sponsor #1234 trial, the Fictitious Medical Group provides the required regulatory documentation to the sponsor.

335 Following trial set up, Patricia contacts Corey Jones, a patient at Fictitious, about participating in the trial and Corey agrees to participate as a subject. A number of tasks deal with this individual patient:

1. Obtain proper consent and other documentation from study candidate Corey Jones.
2. Register Corey in the EHR as a candidate in trial #1234, using the EHR's patient index.
3. Register Corey as a candidate in the EDC system.
- 340 4. Schedules Corey's study screening visits using the EHR scheduling module, and flag the visits as pertaining to the trial #1234.
5. Examine screening results to confirm continued enrollment in the trial.
6. After screening, Patricia obtains and schedules the next set of study activities corresponding to the path (arm) of the Sponsor #1234 trial.

345 Post conditions

1. Fictitious Medical Group uses an EHR and the EDC system to document the Sponsor #1234 trial activities.

After RPE

Preconditions

- 350
1. A Clinical Research Protocol is defined by the clinical trials expert at Sponsor using a study design tool.
 2. The resulting study design definition document is stored and made available for access by a Process Definition Manager (implemented by an EDC or other system).

- 355
3. A Process State Manager (implemented by an EDC or other system) is available to deploy, run and manage the execution of the clinical trial process.
 4. The Fictitious EHR (or other system) can implement the Process Activity Executor role.

Clinical Research Site's Involvement:

Initial:

- 360
1. The Process Activity Executor uses the Retrieve Process Definitions transaction to obtain a list of protocols from the Process Definition Manager.

Screening:


- 365
1. Process Activity Executor uses the Initiate Process transaction to notify the Process State Manager that the site wishes to enter a patient into the study.
 2. Process Activity Executor uses the Retrieve Activities transaction to obtain from the Process State Manager the set of screening activities.
 3. Process Activity Executor uses the Update Activity transaction to send the Process State Manager the screening results. (Note: if activities have associated RFD forms then Update Activity may be replaced by RFD form retrieval and submission.)
 4. Process State Manager uses the Send Process State Alert transaction to notify the Process Activity Executor that the patient passed screening and has been enrolled in the trial.
- 370

Treatment:

- 375
1. Process Activity Executor uses the Retrieve Activities transaction again to obtain from the Process State Manager the next set of study activities for this patient.
 2. Process Activity Executor uses the Update Activity transaction to send the Process State Manager updates of activities as they are performed. (Note: if activities have associated RFD forms then Update Activity may be replaced by RFD form retrieval and submission.)
 3. Process Activity Executor can, at any time, use the Send Process State Alert transaction to notify the Process State Manager that the patient has withdrawn from the trial.
 4. Process State Manager can at any time use the Send Process State Alert transaction to notify the Process Activity Executor that the trial has been placed on hold.
- 380

X.4.2 Process Flow

The basic process flow for RPE is shown below:



385

Figure X.4.2-1: Basic Process Flow in RPE Profile

1. The Process Activity Executor retrieves process definitions of potential interest from the Process Definition Manager.
- 390 2. The Process State Manager may have previously retrieved the same process definition(s) from the same or different Process Definition Manager.
3. The Process Activity Executor requests process initiation by the Process State Manager forwarding a given process definition identifier as well as other required data, e.g., a patient identifier, demographics or eligibility criteria.
- 395 4. The Process State Manager notifies the Process Activity Executor that the process is actively proceeding or otherwise, e.g., after initial screening of patient data.
5. The Process Activity Executor retrieves the current activity it has to perform.
6. After completion of an activity, the Process Activity Executor sends the Process State Manager the updated activity state and output data.

- 400 7. The Process Activity Executor can always notify the Process State Manager of
 unscheduled events that may affect the process state, e.g., patient withdrawal from a
 clinical trial.

X.5 RPE Security Considerations

405 The risk analysis for RPE enumerates assets, threats, and mitigations. The complete risk data is
 stored and available from IHE³.

410 The purpose of this risk assessment is to notify vendors of some of the risks that they are advised
 to consider when implementing RPE actors. For general IHE risks and threats, please see ITI TF-
 1: Appendix L. The vendor is also advised that many risks cannot be mitigated by the IHE
 profile and instead responsibility for mitigation is transferred to the vendor, and occasionally to
 the affinity domains, individual enterprises and implementers. In these instances, IHE fulfills its
 responsibility to notify affected parties through the use of the following sections.

Table X.5-1: Risk Issues

Risk Scenario	Type of Impact	Probability
S1: Patient is misidentified during process initiation, activity retrieval initiation or update. Demographic or identification information is intermixed with that of another patient.	Loss of Data Integrity resulting in potentially incorrect diagnosis, treatment and/or data analysis, possibly resulting in loss of life or quality of life for the patient and/or errant analysis in the context of research, public health or quality processes.	M
S2: A malicious attacker may attempt to compromise the system to obtain wrongful access to patient identity, clinical, financial or insurance data.	Loss of Privacy, Legal Liability / Compensation, Loss / Decrease of Funding, Loss of Public Trust or Reputation for Patient, Provider, Agency, Institution or Organization, Accountable Employee Loses Job	M
S3: Accidental release of personal health information (PHI) protected by consent agreements, regulation or law.	Loss of Privacy, Legal Liability / Compensation, Loss / Decrease of Funding, Loss of Public Trust or Reputation for Patient, Provider, Agency, Institution or Organization, Accountable Employee Loses Job	M
S4: Activity results data with negative indications may be prematurely exposed to patient prior to direct communication.	Decreased Effectiveness of Provider, Agency, Institution or Organization in the conduct of its processes.	M
S5: Identify of certain profile actors needs to be kept secret during conduct of a process, e.g., a double-blind study.	Decreased Effectiveness of Provider, Agency, Institution or Organization in the conduct of its processes.	M

³ The full risk analysis data may be found at:
[ftp://ftp.ihe.net/Quality/2010_2011_YR_4/QRPH%20Technical%20Committee/Maintenance%20work/RPE/RPE Risk Analysis 2010-05-21.xls](ftp://ftp.ihe.net/Quality/2010_2011_YR_4/QRPH%20Technical%20Committee/Maintenance%20work/RPE/RPE%20Risk%20Analysis%202010-05-21.xls)

Risk Scenario	Type of Impact	Probability
S6: In the event of inappropriate disclosure or other incident, auditing and investigation time becomes prohibitively long.	Increased Cost and Decreased Effectiveness of Provider, Agency, Institution or Organization in the conduct of its processes.	M

415 **X.5.1 Recommendations**

The high impact risks include:

- mismatch between patient and patient data
- malicious system attack
- inappropriate or premature disclosure of personal health information
- patient and organization identity protection

420

For risk mitigation, the following profiles from the ITI-TF are referred:

- Audit Trail and Node Authentication (ATNA)
- Basic Patient Privacy Consents (BPPC)
- Cross-Enterprise User Assertion (XUA)
- Consistent Time (CT)
- Enterprise User Authentication (EUA)
- Document Digital Signature (DSG)

425

This profile includes the mitigations:

M1: Ensure additional demographics are available to verify patient identity (e.g., address, other identifiers)

430

M2: Identify actors, ensure secure login and access control to protected data, e.g., using XUA and grouping with EUA for protected applications.

M3: Use secured communication for any patient data e.g., as per ATNA.

M4: Audit access to PHI, e.g., as per ATNA.

435

M5: Obtain patient consent to release protected data, e.g., using BPPC and DSG.

M6: Use pseudonymized identifiers for organizations in transactions as supported by RPE.

These mitigations are transferred to vendors and clients:

T1: Verify demographics other than patient name, birth date and gender.

T2: Providers evaluate and review activity data before submission to ensure data is entered correctly for the correct patient. Providers are cautioned not to use RPE for unmediated treatment

440

or diagnosis, i.e., a doctor must always intervene prior to treatment or diagnosis to ensure that errors that may occur in submission are checked by a human prior to engaging in any treatment or diagnosis of a patient.

T3: Secure internal networks from unauthorized access.

445 **T4:** Ensure strong password use for applications with access to PHI.

T5: Employ a restrictive RBAC scheme for applications providing access to PHI.

T6: Obtain patient consents and ensure patient data requiring increased protection is clearly identified.

450 **T7:** Workflow processes should be designed to ensure provider to patient communication occurs prior to sharing results with negative implications.

T8: Assign pseudonymized identifiers in processes when it is required to shield real identities.

T9: Actors are advised to consider the usability of their logging and audit repository implementation.

X.6 RPE Version mapping

455 The following tables specify mappings from the original Retrieve *Protocol* for Execution to the new Retrieve *Process* for Execution to assist implementers in translating their original RPE actors, transactions, and parameters to the new actors, transactions, and parameters.

Table X.6-1: Actor Mapping

Retrieve <i>Protocol</i> for Execution Actor	Retrieve <i>Process</i> for Execution Actor
ProtocolDefManager	Process Definition Manager
ProtocolExecutor	Process Activity Executor
ProtocolStateManager	Process State Manager

460

Table X.6-2: Transaction Mapping

Retrieve <i>Protocol</i> for Execution Transaction	Retrieve <i>Process</i> for Execution Transaction
RetrieveProtocolDef – Retired [QRPH-10]	Retrieve Process Definitions [QRPH-20]
EnterPatientRequest – Retired [QRPH-11]	Initiate Process [QRPH-25]
PatientScreeningVisitsScheduled – Retired [QRPH-12]	UpdateActivity [QRPH-27]
RecordPatientScreeningVisit – Retired [QRPH-13]	UpdateActivity [QRPH-27]
EnrollPatientRequest – Retired [QRPH-14]	Send Process State Alert [QRPH-28]
PatientStudyVisitsScheduled – Retired [QRPH-15]	UpdateActivity [QRPH-27]

Retrieve <i>Protocol</i> for Execution Transaction	Retrieve <i>Process</i> for Execution Transaction
RecordPatientStudyVisit – Retired [QRPH-16]	UpdateActivity [QRPH-27]
AmendProtocolDef – Retired [QRPH-17]	Publish Process Definitions [QRPH-22]
AlertProtocolState – Retired [QRPH-18]	Send Process State Alert [QRPH-28]

Table X.6-3: Parameter Mapping

Retrieve <i>Protocol</i> for Execution Parameter	Retrieve <i>Process</i> for Execution Parameter
query	processDefinitionIdentifier
ProtocolDefs	processDefinition
contentType	processDefinitionLanguage
study/id	processDefinitionIdentifier
subjectID	processIdentifier
schedule	activity
visit	activity

465 **Appendix A: Actor Summary Definitions**

Process Definition Manager – A system that manages access to a repository of process definitions allowing for search and retrieval. An example would be a research sponsor providing access to the clinical research protocols it has developed. Another would be a provider of evidence-based clinical practice guidelines.

470 **Process State Manager** – A system that manages the initiation and state of runtime process instances. The Process State Manager typically also supports the initiation and lifecycle management of task activities associated with a process while providing the ability for task performers to retrieve and update activities. An example would be a research sponsor conducting clinical trials in conjunction with its EHR participants. Another would be an EHR performing
475 clinical care in accord with executable guideline-based processes.

Process Activity Executor – A system that performs activities as prescribed by a running process being managed by a Process State Manager. The Process Activity Executor retrieves current activity or task lists, works its list, updating the Process State Manager on activity state until completion. This cycle is repeated until all process activities have been worked and the
480 process itself completes. An example would be an EHR performing activities as part of a clinical trial being managed by a research sponsor. Another would be an EHR performing guideline-based care process activities.

Appendix B: Transaction Summary Definitions

485 **Retrieve Process Definitions** – enables access to one or more process definitions specified by an identifier or other query criteria. This transaction is implemented by the Process Definition Manager and used by both the Process State Manager – to deploy processes it wishes to manage – and the Process Activity Executor – to examine processes it may be interested in becoming an activity participant.

490 **Initiate Process** – enables a Process Activity Executor to initiate a new process to be managed by a Process State Manager, e.g., an EHR entering a new patient candidate in a clinical trial being managed by a research sponsor.

Retrieve Activities – enables a Process Activity Executor to retrieve the current set of activities it needs to execute as part of a process managed by a Process State Manager.

495 **Update Activity** – allows a Process Activity Executor to provide an update on activity’s state or data to a Process State Manager for a process it is a participant in.

Send Process State Alert – provides the Process State Manager and Process Activity Executor the ability to notify each other of unscheduled events that affect the state of the process, e.g., an EHR patient withdrawing from a clinical trial or, a study being placed on hold.

500 **Glossary**

Add the following terms to the Glossary:

Process Definition – A designed flow of activities involving one or more role-based activity performers, implemented in XML and deployable to a runtime process consumer.

Process – A specific instance of a process definition running in a process consumer.

505 **Activity Definition** – A designed task which is deployable to a runtime activity processor, typically as part of a process definition.

Activity – A specific instance of an activity definition created in, and available from, an activity processor.

510

Volume 2 - Transactions

3 IHE Transactions

Add Section 3.Y

515 3.Y1 Retrieve Process Definitions



This section corresponds to transaction QRPH-20 of the IHE QRPH Transaction Framework. QRPH-20 is used by the Process Definition Manager and Process Activity Executor Actors.

3.Y1.1 Scope

520 This transaction involves a Process Activity Executor or Process State Manager requesting one or more process definitions from a Process Definition Manager. The Process Activity Executor or Process State Manager has one or more process definition identifiers obtained by means outside the scope of this profile.

The Process Definition Manager returns either a list of matching process definitions or an error response.

525 3.Y1.2 Use Case Roles



530

Actor: Process Activity Executor

Role: A system that knows how to execute activities that are part of a process.

535 **Actor:** Process State Manager

Role: A system that manages the runtime state of a process.

Actor: Process Definition Manager

Role: A system that provides a set of process definitions upon request.

3.Y1.3 Referenced Standards

540 Implementers of this transaction shall comply with all requirements described in:

- ITI TF-2x: Appendix V Web Services for IHE Transactions
- Extensible Markup Language (XML) 1.0 (Second Edition). W3C Recommendation 6 October 2000. <http://www.w3.org/TR/REC-xml>


Implementers of this transaction shall comply with *one of the following* reference standards:

545 • OMG Business Process Model and Notation (BPMN) Version 2.0
[\[http://www.omg.org/spec/BPMN/2.0/\]](http://www.omg.org/spec/BPMN/2.0/)

OR

550 • HL7® Study Design
[\[http://www.hl7.org/v3ballot/html/domains/uvrt/uvrt_StudyDesign.htm\]](http://www.hl7.org/v3ballot/html/domains/uvrt/uvrt_StudyDesign.htm) **AND** HL7®
Study Participation
[\[http://www.hl7.org/v3ballot/html/domains/uvrt/uvrt_StudyParticipation.htm\]](http://www.hl7.org/v3ballot/html/domains/uvrt/uvrt_StudyParticipation.htm)

555 3.Y1.4 Interaction Diagram



560 **3.Y1.4.1 Retrieve Process Definitions Message**

3.Y1.4.1.1 Trigger Events

The Process Activity Executor or Process State Manager, based on human decision or the application of a rule for automatic operation, wants to obtain from the Process Definition Manager one or more process definitions matching a set of previously supplied identifiers.

565 **3.Y1.4.1.2 Message Semantics**

The following parameters are specified for the body of this transaction.

Table 3.Y1.4.1.2-1: Retrieve Process Definitions Request Parameters

Parameter Name	REQ	Description	Value
processDefinitionIdentifier (list)	R	An identifier (or list of identifiers) for the process definition(s) to be retrieved.	HL7 element of type InstanceIdentifier.

Parameter Name	REQ	Description	Value
maxOccurs	O	If specified, the number of process definitions returned MUST NOT exceed this limit.	An XML element of simple type int.
startIndex	O	The startIndex can be used to perform multiple identical queries and iterate over result sets where the maxOccurs size exceeds the query limit.	An XML element of simple type int.

570 Section 3.Y1.6 describes the Web Services protocol requirements and the format of the message in full detail.

3.Y1.4.1.3 Expected Actions

575 Upon reception of the Retrieve Process Definitions Message, the Process Definition Manager shall parse the request and return the requested process definitions in the Retrieve Process Definitions Response message.

The successful response shall be one or more well-formed XML documents matching the supplied identifiers.

Otherwise SOAP faults shall be generated accordingly:

- 580 • If there is missing information, such as no process definition identifier list or the request is otherwise malformed, the fault should include:
 - faultcode: Client
 - faultstring: Invalid Request
 - and may provide further information in the details element.
- 585 • If no matching process definition is available the fault should include:
 - faultcode: Client
 - faultstring: No Matching Process Definition

3.Y1.4.2 Retrieve Process Definitions Response Message

3.Y1.4.2.1 Trigger Events

590 The delivery of a set of process definitions is triggered by a Process Definition Manager Actor in response to a Retrieve Process Definitions message.

3.Y1.4.2.2 Message Semantics

A matching list of one or more process definitions is returned. The format of each process definition is a well-formed XML document.

595

Table 3.Y1.4.1.2-2: Retrieve Process Definitions Response Parameter

Parameter Name	REQ	Description	Value
processDefinition	R	One process definition per process definition identifier requested.	A complex XML element of type specified per optional processDefinitionLanguage attribute
processDefinitionLanguage	R	XML attribute	Options: http://www.omg.org/spec/BPMN/2.0/ (BPMN) PORT_RM100002UV (HL7 StudyDesign)

3.Y1.4.2.3 Expected Actions

The Process Activity Executor shall consume the set of process definitions. If a SOAP fault is received then this fault should be handled based on the business rules of the system.

600

3.Y1.5 Security Considerations

See QRPH TF-1:X.5.

3.Y1.6 Protocol Requirements

605

The Retrieve Process Definitions Request and Response shall be transmitted using Synchronous Web Services Exchange, according to the requirements specified in ITI TF-2x: Appendix V Web Services for IHE Transactions.

Table 3.Y1.6-1: WSDL Namespace Definitions

ihe	urn:ihe:qrph:rpe:2009
soap12	http://schemas.xmlsoap.org/wsdl/soap12/
wsaw	http://www.w3.org/2005/08/addressing
xsd	http://www.w3.org/2001/XMLSchema

610

These are the requirements for the Retrieve Process Definitions transaction presented in the order in which they would appear in the WSDL definition:

615

- The following types shall be imported (xsd:import) in the /definitions/types section:
- namespace="urn:ihe:qrph:rpe:2009", schema="RPE.xsd"
- The /definitions/message/part/@element attribute of the Retrieve Process Definitions Request message shall be defined as: "ihe:RetrieveProcessDefinitionsRequest"
- The /definitions/message/part/@element attribute of the Retrieve Process Definitions Response message shall be defined as: "ihe:RetrieveProcessDefinitionsResponse"

- The /definitions/portType/operation/input/@wsaw:Action attribute for the Retrieve Process Definitions Request message shall be defined as “urn:ihe:qrph:2009:RetrieveProcessDefinitions”
- The /definitions/portType/operation/output/@wsaw:Action attribute for the Retrieve Process Definitions response message shall be defined as: “urn:ihe:qrph:2009:RetrieveProcessDefinitionsResponse”
- The /definitions/binding/operation/soap12:operation/@soapAction attribute shall be defined as “urn:ihe:qrph:2009:RetrieveProcessDefinitions”

620

625

These are the requirements that affect the wire format of the SOAP message. The other WSDL properties are only used within the WSDL definition and do not affect interoperability. Full sample request and response messages are in Section 3.Y1.6.1 Sample SOAP Messages.

3.Y1.6.1 Sample SOAP Messages

630

The samples in the following two sections show a typical request and corresponding response as contained in a SOAP Body. *Note: the SOAP Header should be populated according to the IHE ITI TF-2x: Appendix V: Web Services for IHE Transactions.*

A full WSDL for the Process Definition Manager Actor is found on the IHE FTP site at: ftp://ftp.ihe.net/Quality/2011_2012_YR_5/QRPH_Technical_Committee/Profiles_in_Progress/RPE/metadata

635

3.Y1.6.1.1 Sample Retrieve Process Definitions SOAP Request

Note to the editor: please keep the following format for the sample text – courier new, 8pt, no spacing before and after the paragraph, tab stops every 1/8 of an inch for the first inch.

640

```
<soap:Body>
  <rpe:RetrieveProcessDefinitionsRequest xmlns:rpe="urn:ihe:qrph:rpe:2009">
    <rpe:processDefinitionIdentifier root="1.2.3.4" extension="1006" />
  </rpe:RetrieveProcessDefinitionsRequest>
</soap:Body>
```

645

3.Y1.6.1.2 Sample Retrieve Process Definitions SOAP Response

Note to the editor: please keep the following format for the sample text – courier new, 8pt, no spacing before and after the paragraph, tab stops every 1/8 of an inch for the first inch.

650

```
<soap:Body>
  <rpe:RetrieveProcessDefinitionsResponse xmlns:rpe="urn:ihe:qrph:rpe:2009">
    <rpe:processDefinition processDefinitionLanguage="http://www.omg.org/spec/BPMN/2.0/">
      <definitions targetNamespace="http://www.examples.org"
        xmlns:tns="http://www.examples.org" xmlns="http://www.omg.org/spec/BPMN/20100524/MODEL"
        xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
        xsi:schemaLocation="http://www.omg.org/spec/BPMN/20100524/MODEL BPMN-20100501/BPMN20.xsd
        xmlns:di="http://www.omg.org/spec/DD/20100524/DI
        xmlns:bpmndi="http://www.omg.org/spec/BPMN/20100524/DI"
        xmlns:dc="http://www.omg.org/spec/DD/20100524/DC xmlns:hl7="urn:hl7-org:v3"
        xmlns:rpe="urn:ihe:qrph:rpe:2009" id="_1312929184333">
```

660

```
        <!-- Import schemas and define RPE and HL7 element items for reference by process
665 data object variables -->
        <import importType="http://www.w3.org/2001/XMLSchema" location="RPE.xsd"
        namespace="urn:ihe:qrph:rpe:2009"/>
        <import importType="http://www.w3.org/2001/XMLSchema" location="HL7-
670 SD/StudyDesign.xsd" namespace="urn:hl7-org:v3"/>
        <itemDefinition id="InitiateProcessRequestItem"
        structureRef="rpe:InitiateProcessRequest"></itemDefinition>
        <itemDefinition id="RequestContextItem"
        structureRef="rpe:requestContext"></itemDefinition>
        <itemDefinition id="PatientDataItem"
675 structureRef="rpe:patientData"></itemDefinition>
        <itemDefinition id="EligibilityCriterionItem"
        structureRef="hl7:eligibilityCriterion"></itemDefinition>
        <itemDefinition id="ObservationItem"
        structureRef="hl7:observation"></itemDefinition>
680 <itemDefinition id="SubstanceAdministrationItem"
        structureRef="hl7:substanceAdministration"></itemDefinition>

        <message id="InitiateProcessRequest" itemRef="tns:InitiateProcessRequestItem"
        name="Initiate Process Request"/>

685 <process isExecutable="false" id="_6" name="IHE RPE Study Design" >
        <documentation id="Title">IHE RPE Study Design</documentation>
        <documentation id="Description">A simple single arm example consisting of
        Screen, Treatment and Followup epochs with 3 activities total:
690 later.</documentation>
        <ioSpecification>
        <dataInput isCollection="true" name="Eligibility Criteria"
        id="EligibilityCriteria" itemSubjectRef="tns:EligibilityCriterionItem"/>
695 <dataInput name="Request Context" id="RequestContext"
        itemSubjectRef="tns:RequestContextItem"/>
        <dataInput name="Patient Data" id="PatientData"
        itemSubjectRef="tns:PatientDataItem"/>
        <dataInput name="Substance Administration" id="SubstanceAdministration"
        itemSubjectRef="tns:SubstanceAdministrationItem"/>
700 <dataOutput isCollection="true" name="Screening Observations"
        id="ScreeningObservations" itemSubjectRef="tns:ObservationItem"/>
        <dataOutput isCollection="true" name="Treatment Observations"
        id="TreatmentObservations" itemSubjectRef="tns:ObservationItem"/>
705 <dataOutput isCollection="true" name="Follow-up Observations"
        id="FollowUpObservations" itemSubjectRef="tns:ObservationItem"/>
        ...
        </definitions>
        </rpe:processDefinition>
710 </rpe:RetrieveProcessDefinitionsResponse>
</soap:Body>

<soap:Body>
715 <rpe:RetrieveProcessDefinitionsResponse xmlns:rpe="urn:ihe:qrph:rpe:2009">
        <rpe:processDefinition processDefinitionLanguage="PORT_RM10002UV">
        <plannedStudy xmlns:hl7="urn:hl7-org:v3">
        ...
        </plannedStudy>
720 </rpe:processDefinition>
</rpe:RetrieveProcessDefinitionsResponse>
</soap:Body>
```

3.Y2 Initiate Process

725 This section corresponds to transaction QRPH-25 of the IHE QRPH Transaction Framework. QRPH-25 is used by the Process State Manager and Process Activity Executor Actors.


3.Y2.1 Scope

This transaction involves a Process Activity Executor requesting the initiation of a process with a Process State Manager.

In its request the Process Activity Executor supplies an initial context, including:

- 730
- an identifier for the process definition of interest
 - an organizational identifier
 - a patient identifier
 - an endpoint reference for callback notifications (alerts)
 - other optional patient data (such as demographics)

735 3.Y2.2 Use Case Roles



Actor: Process Activity Executor

740 **Role:** A system that knows how to execute activities that are part of a process.


Actor: Process State Manager

Role: A system that manages the runtime state of a process.

3.Y2.3 Referenced Standards

745 See Section 3.Y1.3.

3.Y2.4 Interaction Diagram



3.Y2.4.1 Initiate Process Message

750 3.Y2.4.1.1 Trigger Events

The Process Activity Executor, based on human decision or the application of a rule for automatic operation, wants to initiate a process with a Process State Manager.

3.Y2.4.1.2 Message Semantics

The following parameters are specified for the body of this transaction.

755

Table 3.Y2.4.1.2-1: Initiate Process Request Parameters

Parameter Name	REQ	Description	Value
patient	R	Basic demographics for the patient.	Simple patient definition, of type rpe:PatientType.
candidateID	R	List of patient identities.	HL7 element of type InstanceIdentifier. HL7 patient name type
name	O	Patient name	HL7 address type
address	O	Patient address	HL7 datetime type
dob	O	Patient date of birth	
processDefinitionIdentifier	R	Identifier for the process definition to be initiated.	HL7 element of type InstanceIdentifier.
processState	R	Initial state of the process	An XML element of type enumerated string.
organizationIdentifier	O	Identifier for the involved organization.	HL7 element of type InstanceIdentifier.
requestorReference	O	The Process Activity Executor callback endpoint for the Process State Manager to use in sending alerts.	WS Addressing EndpointReferenceType

Parameter Name	REQ	Description	Value
patientData	O	Patient data, e.g., a CRD-conforming CCD.	An XML element of complex type specified per patientDataLanguage attribute with default value (CCD): http://xreg2.nist.gov:8080/hitspValidation/schema/cdar2c32/infrastructure/cda/C32_CDA.xsd

Section 3.Y2.6 describes the Web Services protocol requirements and the format of the message in full detail.

760 **3.Y2.4.1.3 Expected Actions**

The Process State Manager parses the Initiate Process request and, if well-formed, initiates an instance of the given process and acknowledges the request with a returned process context to be used in subsequent transactions.

Otherwise SOAP faults shall be generated accordingly:

- 765
- If request is not well-formed, a SOAP fault shall be generated and shall include:
 - faultcode: Client
 - faultstring: Invalid Request
 - and may provide further information in the details element.
 - If the process failed to initiate due to a Process State Manager system error, a SOAP fault shall be generated and shall include:
 - faultcode: Server
 - faultstring: System Error
 - and may provide further information in the details element.
- 770

3.Y2.4.2 Initiate Process Response Message

775 **3.Y2.4.2.1 Trigger Events**

The message is triggered by a Process State Manager receiving an Initiate Process request from a Process Activity Executor and after successful initiation of the process.

3.Y2.4.2.2 Message Semantics

The following output parameters are the body of the response.

780

Table 3.Y2.4.2.2-1: Initiate Process Response Parameters

Parameter Name	REQ	Description	Value
processIdentifier	R	Identifier for process instance	HL7 element of type

Parameter Name	REQ	Description	Value
			InstanceIdentifier.
processState	R	Initial state of the process	An XML element of type enumerated string.
assignedOrganizationIdentifier	O	Assigned identifier for organization.	HL7 element of type InstanceIdentifier.
patient	O	Provided if additional identifiers are assigned to the patient.	Simple patient definition, of type rpe:PatientType.

3.Y2.4.2.3 Expected Actions

785 The Process Activity Executor shall consume the response code based on the business rules of the system. If a SOAP fault is received then this fault should also be handled based on the business rules of the system.

3.Y2.5 Security Considerations

See QRPH TF-1:X.5.

3.Y2.6 Protocol Requirements

790 The Initiate Process request and response shall be transmitted using Synchronous Web Services Exchange, according to the requirements specified in ITI TF-2x: Appendix V Web Services for IHE Transactions.

Table 3.Y2.6-1: WSDL Namespace Definitions

ihe	urn:ihe:qrph:rpe:2009
soap12	http://schemas.xmlsoap.org/wsdl/soap12/
wsaw	http://www.w3.org/2005/08/addressing
xsd	http://www.w3.org/2001/XMLSchema

795

These are the requirements for the Initiate Process transaction presented in the order in which they would appear in the WSDL definition:

- The following types shall be imported (xsd:import) in the /definitions/types section:
- namespace="urn:ihe:qrph:rpe:2009", schema="RPE.xsd"
- 800 • The /definitions/message/part/@element attribute of the Initiate Process Request message shall be defined as: "ihe:InitiateProcessRequest"
- The /definitions/message/part/@element attribute of the Initiate Process Response message shall be defined as: "ihe:InitiateProcessResponse"

- 805
- The /definitions/portType/operation/input/@wsaw:Action attribute for the Initiate Process request message shall be defined as “urn:ihe:qrph:2009:InitiateProcess”
 - The /definitions/portType/operation/output/@wsaw:Action attribute for the Initiate Process response message shall be defined as:
“urn:ihe:qrph:2009:InitiateProcessResponse”
 - The /definitions/binding/operation/soap12:operation/@soapAction attribute shall be defined as “urn:ihe:qrph:2009:InitiateProcess”
- 810

These are the requirements that affect the wire format of the SOAP message. The other WSDL properties are only used within the WSDL definition and do not affect interoperability. Full sample request and response messages are in the Section 3.Y2.6.1 Sample SOAP Messages.

3.Y2.6.1 Sample SOAP Messages

815 The samples in the following two sections show a typical request and corresponding response as contained in a SOAP Body. Note: the SOAP Header should be populated according to the IHE ITI TF-2x: Appendix V: Web Services for IHE Transactions and in accord with Section 3.Y2.5 Security Considerations.

820 A full WSDL for the Process State Manager Actor is found on the IHE FTP site at:
ftp://ftp.ihe.net/Quality/2011_2012_YR_5/QRPH_Technical_Committee/Profiles_in_Progress/RPE/metadata

3.Y2.6.1.1 Sample Initiate Process SOAP Request

Note to the editor: please keep the following format for the sample text – courier new, 8pt, no spacing before and after the paragraph, tab stops every 1/8 of an inch for the first inch.

825

```

830 <soap:Body>
      <rpe:InitiateProcessRequest xmlns:rpe="urn:ihe:qrph:rpe:2009" xmlns:hl7="urn:hl7-org:v3"
      xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/03/addressing">
        <rpe:patient>
          <rpe:candidateID root="" extension="" />
          <rpe:name>
            <hl7:given>John</hl7:given>
            <hl7:family>Smith</hl7:family>
          </rpe:name>
          <rpe:address />
          <rpe:dob value="19990101" />
        </rpe:patient>
        <rpe:processDefinitionIdentifier root="1.2.3.4" extension="1006" />
        <rpe:processState>INTERESTED</rpe:processState>
        <rpe:organizationIdentifier root="1.2.3.5" extension="CIS_CE_CB" />
        <rpe:requestorReference>
          <wsa:Address>http://example.com/fabrikam/acct</wsa:Address>
        </rpe:requestorReference>
845 </rpe:InitiateProcessRequest>
    </soap:Body>

```

3.Y2.6.1.2 Sample Initiate Process SOAP Response

Note to the editor: please keep the following format for the sample text – courier new, 8pt, no spacing before and after the paragraph, tab stops every 1/8 of an inch for the first inch.

850

```
<soap:Body>
  <rpe:InitiateProcessResponse xmlns:rpe="urn:ihe:qrph:rpe:2009">
    <rpe:processIdentifier root="1.2.3.5" extension="1006-1" />
    <rpe:processState>INTERESTED</rpe:processState>
  </rpe:InitiateProcessResponse>
</soap:Body>
```

855

3.Y3 Retrieve Activities

860

This section corresponds to transaction QRPH-26 of the IHE QRPH Transaction Framework. QRPH-26 is used by the Process State Manager and Process Activity Executor Actors.

3.Y3.1 Scope


865

The Retrieve Activities transaction enables a Process Activity Executor to retrieve the current set of activities it needs to execute as part of processes in which it is a participant and which are managed by the given Process State Manager.

In its request, the Process Activity Executor supplies the current process context, per Table 3.Y2.4.2.2.

3.Y3.2 Use Case Roles

870



Actor: Process Activity Executor

Role: A system that knows how to execute activities that are part of a process.

Actor: Process State Manager


875

Role: A system that manages the runtime state of a process.

3.Y3.3 Referenced Standards

See Section 3.Y1.3.

3.Y3.4 Interaction Diagram



880

3.Y3.4.1 Retrieve Activities Message

3.Y3.4.1.1 Trigger Events

The Process Activity Executor, based upon human decision or application of a rule for automatic operation, wants to retrieve the current set of process activities it needs to perform from a Process State Manager.

885

3.Y3.4.1.2 Message Semantics

The current process context (see Table 3.Y2.4.2.2) is the sole input.

Section 3.Y3.6 describes the Web Services protocol requirements and the format of the message in full detail.

3.Y3.4.1.3 Expected Actions

The Process State Manager parses the Retrieve Activities Request message and, if well-formed, returns the current set of activities for the given organization and patient. If no activities are outstanding an empty response is returned.

Otherwise SOAP faults shall be generated accordingly:

- 895
- If the request is not well-formed, a SOAP fault shall be generated and shall include:
 - faultcode: Client
 - faultstring: Invalid Request
 - and may provide further information in the details element.
 - If there is no matching process identifier for the organization, a SOAP fault shall be generated and shall include:
- 900

- faultcode: Client
- faultstring: No Matching Process
- If the supplied process has previously completed or otherwise terminated, a SOAP fault shall be generated and shall include:

905

- faultcode: Client
- faultstring: Process Terminated

3.Y3.4.2 Retrieve Activities Response Message

3.Y3.4.2.1 Trigger Events

910 The message is triggered by a Process State Manager in response to a Retrieve Activities Request from a Process Activity Executor.

3.Y3.4.2.2 Message Semantics

A list of zero or more process activities is returned. The format of each activity is a well-formed XML document of the type supported by the process of which they are part.

915

Table 3.Y3.4.2.2-1: Retrieve Activities Response Parameters

Parameter Name	REQ	Description	Value
activity	R	Current process activity	A complex XML element representing an activity within a process as specified per the activityLanguage attribute
activityLanguage	R	XML attribute	Options: http://www.omg.org/spec/BPMN/2.0.2/PDF/ (BPMN) PORT_RM100002UV (HL7 StudyDesign)
processIdentifier	R	Identifier for process instance	HL7 element of type InstanceIdentifier.
processState	R	Initial state of the process	An XML element of type enumerated string.
assignedOrganizationIdentifier	O	Assigned identifier for organization.	HL7 element of type InstanceIdentifier.
patient	O	Provided if additional identifiers are assigned to the patient.	Simple patient definition, of type rpe:PatientType.

3.Y3.4.2.3 Expected Actions

The Process Activity Executor shall consume the list of activities based on the business rules of the system. If a SOAP fault is received then this fault should also be handled based on the business rules of the system.

920 **3.Y3.5 Security Considerations**

See QRPH TF-1:X.5.

3.Y3.6 Protocol Requirements

925 The Retrieve Activities Request and Response messages shall be transmitted using Synchronous Web Services Exchange, according to the requirements specified in ITI TF-2x: Appendix V Web Services for IHE Transactions.

Table 3.Y3.6-1: WSDL Namespace Definitions

ihe	urn:ihe:qrph:rpe:2009
soap12	http://schemas.xmlsoap.org/wsdl/soap12/
wsaw	http://www.w3.org/2005/08/addressing
xsd	http://www.w3.org/2001/XMLSchema

930 These are the requirements for the Retrieve Activities transaction presented in the order in which they would appear in the WSDL definition:

- The following types shall be imported (xsd:import) in the /definitions/types section:
- namespace="urn:ihe:qrph:rpe:2009", schema="RPE.xsd"
- The /definitions/message/part/@element attribute of the Retrieve Activities request message shall be defined as: "ihe:RetrieveActivitiesRequest"
- 935 • The /definitions/message/part/@element attribute of the Retrieve Activities response message shall be defined as: "ihe:RetrieveActivitiesResponse"
- The /definitions/portType/operation/input/@wsaw:Action attribute for the Retrieve Activities request message shall be defined as "urn:ihe:qrph:2009:RetrieveActivities"
- The /definitions/portType/operation/output/@wsaw:Action attribute for the Retrieve Activities response message shall be defined as:
- 940 "urn:ihe:qrph:2009:RetrieveActivitiesResponse"
- The /definitions/binding/operation/soap12:operation/@soapAction attribute shall be defined as "urn:ihe:qrph:2009:RetrieveActivities"

945 These are the requirements that affect the wire format of the SOAP message. The other WSDL properties are only used within the WSDL definition and do not affect interoperability. Full sample request and response messages are in Section 3.Y3.6.1 Sample SOAP Messages.

3.Y3.6.1 Sample SOAP Messages

The samples in the following two sections show a typical request and corresponding response as contained in a SOAP Body. *Note: the SOAP Header should be populated according to the IHE*

950 *Appendix V: Web Services for IHE Transactions and in accord with Section 3.Y3.5 Security Considerations.*

A full WSDL for the Process State Manager Actor is found on the IHE FTP site at: [ftp://ftp.ihe.net/Quality/2011_2012_YR_5/QRPH Technical Committee/Profiles in Progress/RPE/metadata](ftp://ftp.ihe.net/Quality/2011_2012_YR_5/QRPH_Technical_Committee/Profiles_in_Progress/RPE/metadata)

955 3.Y3.6.1.1 Sample Retrieve Activities SOAP Request

Note to the editor: please keep the following format for the sample text – courier new, 8pt, no spacing before and after the paragraph, tab stops every 1/8 of an inch for the first inch.

```

960 <soap:Body>
    <rpe:RetrieveActivitiesRequest xmlns:rpe="urn:ihe:qrph:rpe:2009">
      <rpe:patient>
        <rpe:candidateID root="" extension="" />
        <rpe:name>
965         <hl7:given>John</hl7:given>
          <hl7:family>Smith</hl7:family>
        </rpe:name>
        <rpe:address />
        <rpe:dob value="19990101" />
970      </rpe:patient>
      <rpe:processIdentifier root="1.2.3.5" extension="1006-1" />
      <rpe:processDefinitionIdentifier root="1.2.3.4" extension="1006" />
      <rpe:processState>SCREENING</rpe:processState>
      <rpe:assignedOrganizationIdentifier root="1.2.3.5" extension="CIS_CE_CB" />
975 </rpe:RetrieveActivitiesRequest>
    </soap:Body>

```

3.Y3.6.1.2 Sample Retrieve Activities SOAP Response

Note to the editor: please keep the following format for the sample text – courier new, 8pt, no spacing before and after the paragraph, tab stops every 1/8 of an inch for the first inch.

```

980 <soap:Body>
    <rpe:RetrieveActivitiesResponse xmlns:rpe="urn:ihe:qrph:rpe:2009">
      <rpe:activity activityLanguage="http://www.omg.org/spec/BPMN/2.0/">
985       <userTask xmlns="http://www.omg.org/spec/BPMN/20100524/MODEL"
         implementation="##unspecified" name="Screening Activity" id="ScreeningActivity"/>
      </rpe:activity>
    </rpe:RetrieveActivitiesResponse>
990 </soap:Body>

    <soap:Body>
      <rpe:RetrieveActivitiesResponse xmlns:rpe="urn:ihe:qrph:rpe:2009" xmlns:hl7="urn:hl7-org:v3">
995       <rpe:activity activityLanguage="PORT_RM10001UV">
        <hl7:study>
          <hl7:instantiation>
            <hl7:plannedStudy>
              ""
            </hl7:plannedStudy>
1000          </hl7:instantiation>
        </hl7:study>
      </rpe:activity>
    </rpe:RetrieveActivitiesResponse>
1005 </soap:Body>

```

3.Y4 Update Activity

This section corresponds to transaction QRPH-27 of the IHE QRPH Transaction Framework. QRPH-27 is used by the Process State Manager and Process Activity Executor Actors.


3.Y4.1 Scope

1010 Update Activity allows a Process Activity Executor to provide an update on an activity's state or data to a Process State Manager for a process in which it is a participant.

In its request, the Process Activity Executor supplies the current process context, per table 3.Y2.4.2.2, and the updated activity.

3.Y4.2 Use Case Roles

1015



Actor: Process Activity Executor

Role: A system that knows how to execute activities that are part of a process.


Actor: Process State Manager

1020 **Role:** A system that manages the runtime state of a process.

3.Y4.3 Referenced Standards

See Section 3.Y1.3.

3.Y4.4 Interaction Diagram



1025

3.Y4.4.1 Update Activity Message

3.Y4.4.1.1 Trigger Events

The Process Activity Executor, based upon human decision or application of a rule for automatic operation, wants to update the Process State Manager with the current state or data associated with an activity it is performing.

1030

3.Y4.4.1.2 Message Semantics

The following parameters are specified for the body of this transaction.

Table 3.Y4.4.1.2-1: Update Activity Request Parameters

Parameter Name	REQ	Description	Value
activity	R	One or more process activities.	A complex XML element representing an activity within a process as specified per the activityLanguage attribute
activityLanguage	R	XML attribute	Options: http://www.omg.org/spec/BPMN/2.0.2/PDF/ (BPMN) PORT_RM100002UV (HL7 StudyDesign)
processIdentifier	R	Identifier for process instance	HL7 element of type InstanceIdentifier.
processState	R	State of the process	An XML element of type enumerated string.

Parameter Name	REQ	Description	Value
assignedOrganizationIdentifier	O	Assigned identifier for organization.	HL7 element of type InstanceIdentifier.
patient	O	Provided if additional identifiers are assigned to the patient.	Simple patient definition, of type rpe:PatientType.

1035

Section 3.Y4.6 describes the Web Services protocol requirements and the format of the message in full detail.

3.Y4.4.1.3 Expected Actions

1040

The Process State Manager parses the Update Activity request and if well-formed, updates the given activity for the state and/or data supplied.

If the activity is updated as a result of this transaction the Process State Manager acknowledges the request with a response code of “ACTIVITY_UPDATED”.

Otherwise SOAP faults shall be generated accordingly:

1045

- If the request is not well-formed, a SOAP fault shall be generated and shall include:
 - faultcode: Client
 - faultstring: Invalid Request
 - and may provide further information in the details element.

1050

- If there is no matching activity identifier, a SOAP fault shall be generated and shall include:

- faultcode: Client
- faultstring: No Matching Activity

1055

- If the process failed to update the activity due to a Process State Manager system error, a SOAP fault shall be generated and shall include:
 - faultcode: Server
 - faultstring: System Error
 - and may provide further information in the details element.

3.Y4.4.2 Update Activity Response Message

3.Y4.4.2.1 Trigger Events

1060

The message is triggered by a Process State Manager receiving an Update Activity request from a Process Activity Executor.

3.Y4.4.2.2 Message Semantics

A responseCode XML element of type string is returned which confirms successful update of the activity with a value of “ACTIVITY_UPDATED”.

3.Y4.4.2.3 Expected Actions

1065 The Process Activity Executor shall consume the response code based on the business rules of the system. If a SOAP fault is received then this fault should also be handled based on the business rules of the system.

3.Y4.5 Security Considerations

See Section QRPH TF-1:X.5

1070 3.Y4.6 Protocol Requirements

The Update Activity request and response shall be transmitted using Synchronous Web Services Exchange, according to the requirements specified in ITI TF-2x: Appendix V Web Services for IHE Transactions.

1075

Table 3.Y4.6-1: WSDL Namespace Definitions

ihe	urn:ihe:qrph:rpe:2009
soap12	http://schemas.xmlsoap.org/wsdl/soap12/
wsaw	http://www.w3.org/2005/08/addressing
xsd	http://www.w3.org/2001/XMLSchema

These are the requirements for the Update Activity transaction presented in the order in which they would appear in the WSDL definition:

- The following types shall be imported (xds:import) in the /definitions/types section:
- 1080 • namespace=”urn:ihe:qrph:rpe:2009”, schema=”RPE.xsd”
- The /definitions/message/part/@element attribute of the Update Activity request message shall be defined as: “ihe:UpdateActivityRequest”
- The /definitions/message/part/@element attribute of the Update Activity response message shall be defined as: “ihe:UpdateActivityResponse”
- 1085 • The /definitions/portType/operation/input/@wsaw:Action attribute for the Update Activity request message shall be defined as “urn:ihe:qrph:2009:UpdateActivity”
- The /definitions/portType/operation/output/@wsaw:Action attribute for the Update Activity response message shall be defined as: “urn:ihe:qrph:2009:UpdateActivityResponse”

- 1090
- The /definitions/binding/operation/soap12:operation/@soapAction attribute shall be defined as “urn:ihe:qrph:2009:UpdateActivity”

These are the requirements that affect the wire format of the SOAP message. The other WSDL properties are only used within the WSDL definition and do not affect interoperability. Full sample request and response messages are in the Section 3.Y4.6.1 Sample SOAP Messages.

1095 3.Y4.6.1 Sample SOAP Messages

The samples in the following two sections show a typical request and corresponding response as contained in a SOAP Body. *Note the SOAP Header should be populated according to the IHE Appendix V: Web Services for IHE Transactions and in accord with Section 3.Y4.5 Security Considerations.*

1100 A full WSDL for the Process State Manager Actor is found on the IHE FTP site at: [ftp://ftp.ihe.net/Quality/2011_2012_YR_5/QRPH Technical Committee/Profiles in Progress/RPE/metadata](ftp://ftp.ihe.net/Quality/2011_2012_YR_5/QRPH%20Technical%20Committee/Profiles%20in%20Progress/RPE/metadata).

3.Y4.6.1.1 Sample Update Activity SOAP Request

1105 *Note to the editor: please keep the following format for the sample text – courier new, 8pt, no spacing before and after the paragraph, tab stops every 1/8 of an inch for the first inch.*

```

1105 <soap:Body>
1110   <rpe:UpdateActivityRequest xmlns:rpe="urn:ihe:qrph:rpe:2009">
1115     <rpe:patient>
1120       <rpe:candidateID root="" extension="" />
1125       <rpe:name>
1130         <hl7:given>John</hl7:given>
1135         <hl7:family>Smith</hl7:family>
1140       </rpe:name>
1145       <rpe:address />
1150       <rpe:dob value="19990101" />
1155     </rpe:patient>
1160     <rpe:processIdentifier root="1.2.3.5" extension="1006-1" />
1165     <rpe:processDefinitionIdentifier root="1.2.3.4" extension="1006" />
1170     <rpe:processState>SCREENING</rpe:processState>
1175     <rpe:assignedOrganizationIdentifier root="1.2.3.5" extension="CIS_CE_CB" />
1180     <rpe:activity activityLanguage="http://www.omg.org/spec/BPMN/2.0/">
1185       <userTask xmlns="http://www.omg.org/spec/BPMN/20100524/MODEL"
1190         implementation="##unspecified" name="Screening Activity" id="ScreeningActivity">
1195         <dataOutputAssociation id="ScreeningObservations_DataOutput">
1200           <targetRef>ScreeningObservations</targetRef>
1205           <assignment>
1210             <from><![CDATA[
1215               <hl7:observation xmlns:hl7="urn:hl7-org:v3" classCode="OBS"
1220               moodCode="CRT">
1225                 <id root="1.2.5.2.3.4" extension="DBP"/>
1230                 <code code="8462-4" codeSystem="2.16.840.1.113883.6.1"
1235                 codeSystemName="LOINC" displayName="BP Diastolic">
1240                   <originalText>Diastolic Blood Pressure</originalText>
1245                 </code>
1250                 <statusCode code="active"/>
1255                 <value xsi:type="PQ" value="120" unit="mmHg"/>
1260               </hl7:observation>
1265             </from>
1270           </to>ScreeningObservations</to>
1275         </assignment>

```

```

1145         </dataOutputAssociation>
           </userTask>
         </rpe:activity>
       </rpe:UpdateActivityRequest>
     </soap:Body>
</soap:Body>
1150 <rpe:UpdateActivityRequest xmlns:rpe="urn:ihe:qrph:rpe:2009" xmlns:hl7="urn:hl7-org:v3">
  <rpe:patient>
    <rpe:candidateID root="" extension="" />
    <rpe:name>
1155       <hl7:given>John</hl7:given>
       <hl7:family>Smith</hl7:family>
    </rpe:name>
    <rpe:address />
    <rpe:dob value="19990101" />
  </rpe:patient>
1160 <rpe:processIdentifier root="1.2.3.5" extension="1006-1" />
  <rpe:processDefinitionIdentifier root="1.2.3.4" extension="1006" />
  <rpe:processState>SCREENING</rpe:processState>
  <rpe:assignedOrganizationIdentifier root="1.2.3.5" extension="CIS_CE_CB" />
1165 <rpe:activity activityLanguage="PORT_RM100001UV">
  <hl7:study>
    <hl7:instantiation>
      <hl7:plannedStudy>
        ...
1170      </hl7:plannedStudy>
    </hl7:instantiation>
  </hl7:study>
  </rpe:activity>
</rpe:UpdateActivityRequest >
</soap:Body>

```

1175 3.Y4.6.1.2 Sample Update Activity SOAP Response

Note to the editor: please keep the following format for the sample text – courier new, 8pt, no spacing before and after the paragraph, tab stops every 1/8 of an inch for the first inch.

```

1180 <soap:Body>
  <rpe:UpdateActivityRequestResponse xmlns:rpe="urn:ihe:qrph:rpe:2009">
    <rpe:responseCode>ACTIVITY_UPDATED</rpe:responseCode>
  </rpe:UpdateActivityRequestResponse>
</soap:Body>

```

1185 3.Y5 Send Process State Alert

This section corresponds to transaction QRPH-28 of the IHE QRPH Transaction Framework. QRPH-28 is used by the Process State Manager and Process Activity Executor Actors.

3.Y5.1 Scope

This transaction involves either:


- 1190
- a Process Activity Executor alerting a Process State Manager of a change that affects the state of a process it initiated,

OR

- a Process State Manager alerting a Process Activity Executor of a change associated with a process it initiated with the Process State Manager, in which case the alert contains.

1195 In either case, the request passed by the actor supplies the current process context as per Table 3.Y2.4.2.2 and a process state value.

3.Y5.2 Use Case Roles



1200 **Actor:** Process Activity Executor

Role: A system that knows how to execute activities that are part of a process.


Actor: Process State Manager

Role: A system that manages the runtime state of a process.


3.Y5.3 Referenced Standards

1205 See Section 3.Y1.3.

3.Y5.4 Interaction Diagram



OR



1210

3.Y5.4.1 Send Process State Alert Message

3.Y5.4.1.1 Trigger Events

Either:

- 1215 • the Process Activity Executor, based upon human decision or application of a rule for automatic operation, wants to alert the Process State Manager of a change that affects a process it initiated

OR

- 1220 • the Process State Manager, based upon human decision or application of a rule for automatic operation, wants to alert the Process Activity Executor of a change associated with a process it initiated with the Process State Manager.

3.Y5.4.1.2 Message Semantics

The following parameters are specified for the body of this transaction.

Table 3.Y5.4.1.2-1: Send Process State Alert Request Parameters

Parameter Name	REQ	Description	Value
patient	O	Basic demographics for the patient.	Simple patient definition, of type rpe:PatientType.
processDefinitionIdentifier	R	Identifier for the process definition to be initiated.	HL7 element of type InstanceIdentifier.
processIdentifier	R	Identifier for process instance	HL7 element of type InstanceIdentifier.
processState	R	The process state change being alerted.	An XML element of type enumerated string.
assignedOrganizationIdentifier	O	Assigned identifier for organization.	HL7 element of type InstanceIdentifier.

1225 Section 3.Y5.6 describes the Web Services protocol requirements and the format of the message in full detail.

3.Y5.4.1.3 Expected Actions

1230 The Process Activity Executor or Process State Manager parses the Send Process State Alert request and if well-formed acknowledges the request with a response code of “ALERT_RECEIVED”.

Otherwise SOAP faults shall be generated accordingly:

- If request is not well-formed, a SOAP fault shall be generated and shall include:
 - faultcode: Client
 - faultstring: Invalid Request
- and may provide further information in the details element

1235

3.Y5.4.2 Send Process State Alert Response Message

3.Y5.4.2.1 Trigger Events

The message is triggered by a Process Activity Executor or Process State Manager receiving a well-formed Send Process State Alert request.

1240 **3.Y5.4.2.2 Message Semantics**

A responseCode XML element of type string is returned to confirm receipt of the alert with a value of “ALERT_RECEIVED”.

3.Y5.4.2.3 Expected Actions

1245 The Process Activity Executor or Process State Manager shall consume the response code based on the business rules of the system. If a SOAP fault is received then this fault should also be handled based on the business rules of the system.

3.Y5.5 Security Considerations

See QRPH TF-1:X.5.

3.Y5.6 Protocol Requirements

1250 The Send Process State Alert request and response shall be transmitted using Synchronous Web Services Exchange, according to the requirements specified in ITI TF-2x: Appendix V Web Services for IHE Transactions.

Table 3.Y5.6-1: WSDL Namespace Definitions

ihe	urn:ihe:qrph:rpe:2009
soap12	http://schemas.xmlsoap.org/wsdl/soap12/

wsaw	http://www.w3.org/2005/08/addressing
xsd	http://www.w3.org/2001/XMLSchema

1255

These are the requirements for the Send Process State Alert transaction presented in the order in which they would appear in the WSDL definition:

- The following types shall be imported (xds:import) in the /definitions/types section:
 - namespace="urn:ihe:qrph:rpe:2009", schema="RPE.xsd"
- 1260 • The /definitions/message/part/@element attribute of the Send Process State Alert request message shall be defined as: "ihe:SendProcessStateAlertRequest"
- The /definitions/message/part/@element attribute of the Send Process State Alert response message shall be defined as: "ihe:SendProcessStateAlertResponse"
- 1265 • The /definitions/portType/operation/input/@wsaw:Action attribute for the Send Process State Alert request message shall be defined as "urn:ihe:qrph:2009:SendProcessStateAlert"
- The /definitions/portType/operation/output/@wsaw:Action attribute for the Send Process State Alert response message shall be defined as: "urn:ihe:qrph:2009:SendProcessStateAlertResponse"
- 1270 • The /definitions/binding/operation/soap12:operation/@soapAction attribute shall be defined as "urn:ihe:qrph:2009:SendProcessStateAlert"

These are the requirements that affect the wire format of the SOAP message. The other WSDL properties are only used within the WSDL definition and do not affect interoperability. Full sample request and response messages are in the Section 3.Y5.6.1 Sample SOAP Messages.

1275 **3.Y5.6.1 Sample SOAP Messages**

The samples in the following two sections show a typical request and corresponding response as contained in a SOAP Body. *Note the SOAP Header should be populated according to the IHE Appendix V: Web Services for IHE Transactions and in accord with Section 3.Y5.5 Security Considerations.*

1280 A full WSDL for the Process State Manager Actor is found on the IHE FTP site at: [ftp://ftp.ihe.net/Quality/2011_2012_YR_5/QRPH Technical Committee/Profiles in Progress/RPE/metadata](ftp://ftp.ihe.net/Quality/2011_2012_YR_5/QRPH%20Technical%20Committee/Profiles%20in%20Progress/RPE/metadata).

3.Y5.6.1.1 Sample Send Process State Alert SOAP Request

1285 *Note to the editor: please keep the following format for the sample text – courier new, 8pt, no spacing before and after the paragraph, tab stops every 1/8 of an inch for the first inch.*

```
Process State Manager to Process Activity Executor (notification of patient enrollment):
<soap:Body>
```

```
1290 <rpe:SendProcessStateAlertRequest xmlns:rpe="urn:ihe:qrph:rpe:2009">
      <rpe:patient>
        <rpe:candidateID root="" extension="" />
        <rpe:name>
          <hl7:given>John</hl7:given>
1295         <hl7:family>Smith</hl7:family>
          </rpe:name>
          <rpe:address />
          <rpe:dob value="19990101" />
1300        </rpe:patient>
        <rpe:processIdentifier root="1.2.3.5" extension="1006-1" />
        <rpe:processDefinitionIdentifier root="1.2.3.4" extension="1006" />
        <rpe:processState>ENROLLED</rpe:processState>
        <rpe:assignedOrganizationIdentifier root="1.2.3.5" extension="CIS_CE_CB" />
1305 </rpe:SendProcessStateAlertRequest>
</soap:Body>
```

3.Y5.6.1.2 Sample Send Process State Alert SOAP Response

Note to the editor: please keep the following format for the sample text – courier new, 8pt, no spacing before and after the paragraph, tab stops every 1/8 of an inch for the first inch.

```
1310 <soap:Body>
      <rpe:SendProcessStateAlertResponse xmlns:rpe="urn:ihe:qrph:rpe:2009">
        <rpe:responseCode>ALERT_RECEIVED</rpe:responseCode>
1315 </rpe:SendProcessStateAlertResponse>
</soap:Body>
```