

Integrating the Healthcare Enterprise



5

**IHE IT Infrastructure  
Technical Framework Supplement**

10

**Advanced Patient Privacy Consents  
(APPC)**

15

**Rev. 1.2 – Trial Implementation**

20 Date: July 24, 2018  
Author: IHE ITI Technical Committee  
Email: [iti@ihe.net](mailto:iti@ihe.net)

25

**Please verify you have the most recent version of this document. See [here](#) for Trial Implementation and Final Text versions and [here](#) for Public Comment versions.**

## Foreword

30 This is a supplement to the IHE IT Infrastructure Technical Framework V15.0. Each supplement undergoes a process of public comment and trial implementation before being incorporated into the volumes of the Technical Frameworks.

This supplement is published on July 24, 2018 for trial implementation and may be available for testing at subsequent IHE Connectathons. The supplement may be amended based on the results of testing. Following successful testing it will be incorporated into the IT Infrastructure  
35 Technical Framework. Comments are invited and may be submitted at [http://www.ihe.net/ITI Public Comments](http://www.ihe.net/ITI_Public_Comments).

This supplement describes changes to the existing technical framework documents.

“Boxed” instructions like the sample below indicate to the Volume Editor how to integrate the relevant section(s) into the relevant Technical Framework volume.

40 *Amend Section X.X by the following:*

Where the amendment adds text, make the added text **bold underline**. Where the amendment removes text, make the removed text **~~bold strikethrough~~**. When entire new sections are added, introduce with editor’s instructions to “add new text” or similar, which for readability are not bolded or underlined.

45

General information about IHE can be found at <http://ihe.net>.

Information about the IHE IT Infrastructure domain can be found at [http://ihe.net/IHE Domains](http://ihe.net/IHE_Domains).

Information about the organization of IHE Technical Frameworks and Supplements and the process used to create them can be found at [http://ihe.net/IHE Process](http://ihe.net/IHE_Process) and <http://ihe.net/Profiles>.

50 The current version of the IHE IT Infrastructure Technical Framework can be found at [http://ihe.net/Technical Frameworks](http://ihe.net/Technical_Frameworks).

55 CONTENTS

	Introduction to this Supplement.....	6
	Open Issues and Questions .....	6
	Closed Issues .....	7
60	Glossary .....	8
	<b>Volume 1 – Profiles .....</b>	<b>10</b>
	Copyright Licenses.....	10
	Domain-specific additions .....	10
43	Advanced Patient Privacy Consents (APPC) Profile.....	11
65	43.1 APPC Actors, Transactions, and Content Modules .....	11
	43.1.1 Actor Descriptions and Actor Profile Requirements.....	11
	43.2 APPC Actor Options .....	11
	43.2.1 View Option .....	12
	43.2.2 Structured Policy Processing Option.....	12
70	43.3 APPC Required Actor Groupings .....	12
	43.4 APPC Overview .....	12
	43.4.1 Concepts .....	13
	43.4.2 Use Cases .....	15
	43.4.2.1 Use Case #1: Facility-specific Disclosure.....	15
75	43.4.2.1.1 Facility-specific Disclosure Use Case Description.....	15
	43.4.2.1.2 Facility-specific Disclosure Process Flow .....	16
	43.4.2.2 Use Case #2: Consent for an Episode of Care.....	16
	43.4.2.2.1 Consent for an Episode of Care Use Case Description .....	17
	43.4.2.2.2 Consent for an Episode of Care Process Flow.....	18
80	43.4.2.3 Use Case #3: Consent to Collect from a Specific Service Delivery Location .	18
	43.4.2.3.1 Consent to Collect from a Specific Service Delivery Location Use Case	
	Description.....	18
	43.4.2.3.2 Consent to Collect from a Specific Service Delivery Location Process	
	Flow .....	19
85	43.4.2.4 Use Case #4: Withhold Consent for Information Related to a Specific Order	20
	43.4.2.4.1 Withhold Consent to Disclose Information Related to a Specific Order	
	Use Case Description.....	20
	43.4.2.4.2 Withhold Consent for Information Related to a Specific Order Process	
	Flow .....	21
90	43.4.2.5 Use Case #5: Withhold Consent to Disclose to a Specific Provider	
	Organization .....	22
	43.4.2.5.1 Withhold Consent to Disclose to a Specific Provider Organization Use	
	Case Description .....	22
	43.4.2.5.2 Withhold Consent to Disclose to a Specific Provider Organization Process	
95	Flow .....	23
	43.4.2.6 Use Case #6: Withhold Consent to Disclose a Specific Document .....	23

	43.4.2.6.1 Withhold Consent to Disclose a Specific Document Use Case Description .....	23
	43.4.2.6.2 Withhold Consent to Disclose a Specific Document Process Flow .....	24
100	43.5 APPC Privacy and Security Considerations .....	25
	43.6 APPC Cross Profile Considerations.....	25
	Appendices.....	27
	<b>Volume 2 – Transactions.....</b>	<b>28</b>
	<b>Volume 3 – Content Modules.....</b>	<b>29</b>
105	5 IHE Content Specifications.....	30
	5.6 Advanced Patient Privacy Consents Content Module .....	30
	5.6.1 References .....	30
	5.6.2 Privacy Consent Document Specification.....	30
	5.6.2.1 Content Specification .....	30
110	5.6.2.1.1 Policy Structure .....	31
	5.6.2.1.1.1 Human Readable Representation.....	31
	5.6.2.1.1.2 Example Document.....	32
	5.6.2.1.2 Data Types .....	33
	5.6.2.1.3 Functions.....	33
115	5.6.2.1.4 Attribute Definitions – Subject.....	34
	5.6.2.1.4.1 User ID.....	34
	5.6.2.1.4.2 User Organization .....	35
	5.6.2.1.4.3 User Organization ID .....	36
	5.6.2.1.4.4 User Home Community ID.....	36
120	5.6.2.1.4.5 National Provider Identifier (NPI).....	37
	5.6.2.1.4.6 User Role .....	38
	5.6.2.1.4.7 Purpose Of Use .....	39
	5.6.2.1.4.8 Other Provider Identifier.....	39
	5.6.2.1.5 Attribute Definitions – Resources .....	40
125	5.6.2.1.5.1 Attribute Definitions – General Document Sharing Attributes .....	40
	5.6.2.1.5.1.1 Author Institution ID.....	40
	5.6.2.1.5.1.2 Author Person ID .....	41
	5.6.2.1.5.1.3 Availability Status.....	42
	5.6.2.1.5.1.4 Community ID .....	43
130	5.6.2.1.5.1.5 Patient ID .....	43
	5.6.2.1.5.1.6 Source System ID.....	44
	5.6.2.1.5.2 Attribute Definitions – DocumentEntry Resource.....	45
	5.6.2.1.5.2.1 Class Code.....	45
	5.6.2.1.5.2.2 Confidentiality Code .....	45
135	5.6.2.1.5.2.3 Creation Time.....	46
	5.6.2.1.5.2.4 Event Code.....	46
	5.6.2.1.5.2.5 Healthcare Facility Type Code.....	47
	5.6.2.1.5.2.6 Legal Authenticator.....	48

	5.6.2.1.5.2.7 Practice Setting Code .....	48
140	5.6.2.1.5.2.8 Repository Unique ID .....	49
	5.6.2.1.5.2.9 Reference ID List .....	49
	5.6.2.1.5.2.10 Service Start Time .....	50
	5.6.2.1.5.2.11 Service Stop Time .....	50
	5.6.2.1.5.2.12 Source Patient ID .....	51
145	5.6.2.1.5.2.13 Type Code .....	52
	5.6.2.1.5.2.14 Document Unique ID .....	52
	5.6.2.1.5.2.15 Related Folder Unique ID .....	53
	5.6.2.1.5.2.16 Related Folder Code .....	54
	5.6.2.1.5.2.17 Resource Type .....	54
150	5.6.2.1.5.3 Attribute Definitions - Folder Resource .....	55
	5.6.2.1.5.3.1 Code .....	55
	5.6.2.1.5.3.2 Last Update Time .....	56
	5.6.2.1.5.3.3 Folder UniqueId .....	56
	5.6.2.1.5.3.4 Resource Type .....	57
155	5.6.2.1.5.4 Attribute Definitions - SubmissionSet Resource .....	57
	5.6.2.1.5.4.1 Content Type .....	57
	5.6.2.1.5.4.2 Intended Recipient Id .....	58
	5.6.2.1.5.4.3 Intended Recipient Email .....	58
	5.6.2.1.5.4.4 Submission Time .....	59
160	5.6.2.1.5.4.5 Submission Set Unique ID .....	60
	5.6.2.1.5.4.6 Resource Type .....	61
	5.6.2.1.6 Attribute Definitions – Action .....	61
	5.6.2.1.6.1 Action URIs .....	61
	5.6.2.1.6.2 Additional Action Attribute – Query ID .....	62
165	5.6.2.1.6.3 Additional Action Attribute – Return Type .....	62
	5.6.2.1.7 Attribute Definitions – Environment .....	63
	5.6.2.2 Document Sharing Metadata .....	63
	5.6.2.2.1 XDS DocumentEntry Metadata .....	63
	5.6.2.2.1.1 XDSDocumentEntry.typeCode .....	63
170	5.6.2.2.1.2 XDSDocumentEntry.eventCodeList .....	63
	5.6.2.2.1.3 XDSDocumentEntry.formatCode .....	63
	5.6.2.2.1.4 XDSDocumentEntry.uniqueId .....	64
	5.6.2.2.1.5 XDSDocumentEntry.title .....	64
	5.6.2.2.1.6 XDSDocumentEntry.serviceStartTime .....	64
175	5.6.2.2.1.7 XDSDocumentEntry.serviceStopTime .....	64
	5.6.2.2.1.8 XDSDocumentEntry.referenceIdList .....	64
	5.6.2.2.2 XDS SubmissionSet Metadata .....	64
	5.6.2.2.3 XDS Folder Metadata .....	64
	Volume 3 Namespace Additions .....	66
180		

## Introduction to this Supplement

185 The Advanced Patient Privacy Consents (APPC) Profile defines a structural representation of a privacy consent policy. The definition allows for privacy consent policies that can include individualized parts, based on the patient’s choices.

This profile is intended to allow an unspecified enforcement mechanism, potentially within an existing access control system, to use the structured policy representation to automatically determine and enforce those policies.

## Open Issues and Questions

190 APPC-3: Are there limitations on what metadata or content attributes not defined by the profile can be communicated using a Privacy Consent Document? How are these attributes limited? What does the content consumer with the Structured Policy Processing Option have to understand/support?

195 APPC-4: The human readable consent representation in the XACML document doesn’t contain formatting. The profile addresses this by specifying a linking mechanism (using associations). Is this sufficient or do we need to address this differently?

APPC-5: Should coded values be expressed in a string (or URI format) instead of a structured HL7<sup>®</sup><sup>1</sup>v3 based data type? Which solution helps implementers dealing with code equivalency issues (e.g., ICD-10 vs. ICD-9 representations of the same concept)?

200 APPC-7: Should the profile define a policy-combining and a rule-combining algorithm? Or would picking a fixed combining-algorithm be too restrictive?

205 APPC-8: DateTime conversion algorithm from partial dates (i.e., dates with uncertainty, e.g., “200904” meaning some point in time in April 2009) loses the information that the metadata contained a partial date. Could this negatively impact authorizations? Please suggest language to address this.

210 APPC-10: Should we continue to use a string for the XdsFolder.uniqueId and the XdsSubmissionSet.uniqueId, although they are OIDs? The alternative would be an anyURI data type, but that doesn’t work for document entries. The downside of using the anyURI data type for two of three attributes (which all share the resource-id URN): The data type would then be dependent on whether the resource is a DocumentEntry, a Folder or a SubmissionSet.

APPC-11: Should the document/folder/submissionSet title be available for authorization checks? Does it introduce significant risk of abuse (e.g., regex matching of user entered titles)?

---

<sup>1</sup> HL7 is the registered trademark of Health Level Seven International.

215 APPC-12: The profile doesn't address how to control access to a document based on the metadata or identity of another document. E.g., policy writers cannot express a rule where users are allowed to access a document if they were allowed to access the document it replaced. This restriction applies to all document associations. Is this restriction critical to achieve the goals of the profile?

220 APPC-14: Are the examples that can be found at [ftp://ftp.ihe.net/TF\\_Implementation\\_Material/ITI/examples/APPC](ftp://ftp.ihe.net/TF_Implementation_Material/ITI/examples/APPC) useful to implementors? Please suggest other examples or corrections/improvements to the current ones.

225 APPC-17: Author information from multiple authors cannot be correlated in a policy. This means that it is currently not possible to have a policy that requires an author to have, e.g., a specific identifier and a specific authorRole. The profile mitigates this by limiting author metadata to the authorPerson ID and the authorInstitution ID. Is this restriction to prohibitive?

## Closed Issues

APPC-1: Do we need to have an APPC Enforcement Option in XDS?

- We have given the development of an Enforcement Option for APPC in the XDS Profile (similar to what BPPC did) a very low priority – we will at most attempt to address this at the end, if time allows (Dec 1<sup>st</sup> 2015 Call)

APPC-6: Is there a need for a catch-all action ID that means “any kind of retrieve” (including generic FHIR<sup>®2</sup>-based data access)?

- We will only define action IDs for the IHE Document Sharing transactions to avoid scope creep

235 APPC-2: Should we include a list of supported metadata attributes in volume 1?

- Adding such a table would create maintenance issues

APPC-9: How to distinguish between the user's name and the user's identifier? The identifier doesn't have an URN in XUA. The name URN on the other hand has two variants which are supposed to be semantically equivalent but use two different definitions in XUA and SeR.

- The subject's real name has been removed, as it is not suitable for authorization checks

APPC-13: Appendix P for Vol 2x has not been modified yet and was included in its current (revision 12) final text form. Are extensive updates necessary? Please suggest specific sections that would benefit from updates regarding APPC.

---

<sup>2</sup> FHIR is the registered trademark of Health Level Seven International.

- Removed Appendix P from the supplement, will be added through a separate CP.

245 APPC-15: Should the XACML content be wrapped in a CDA<sup>®3</sup>?

- Wrapping the content in a CDA has been considered and rejected. The overhead of CDA wrapping (less space efficient, more complicated creation and consumption) was considered too high for the perceived benefit (better human readable representation, additional structured metadata describing who consented and how/when) when compared to using a linked document instead.

250

APPC-16: Should we define Obligations (e.g., inform the patient via email when “break-glass” access occurs) to be used in the policies?

- XACML2 does not define standard obligations. Defining new obligations for this profile is difficult without knowing the enforcement environment and therefore, also considered out of scope. Content Creators are free to include obligations in their policies, but APPC does not define these obligations.

255

## Glossary

*Add the following glossary terms to the IHE Technical Frameworks General Introduction Glossary and in the Volume 1 GLOSSARY:*

260

Glossary Term	Definition
Privacy Consent Document	A document containing a structured policy used to express a patient’s privacy preference
Structured Policy	A machine-processible set of access rules that enable the receiving system to enforce the patient’s privacy preferences without requiring human interpretation.

*Replace the definitions for the following glossary terms in the IHE Technical Frameworks General Introduction Glossary and in the ITI TF-1: GLOSSARY:*

Glossary Term	Definition
Patient Privacy Policy	A Patient Privacy Policy will identify who has access to information, and what information is governed by the policy (e.g., under what conditions will a document be marked as containing that type of information). The policy may also describe the patient's rights to specify their consent preferences, notifications, complaints, or requests as well as the mechanism that allows them to do so.

<sup>3</sup> CDA is the registered trademark of Health Level Seven International.



## IHE IT Infrastructure Technical Framework Supplement – Advanced Patient Privacy Consents (APPC)

---

<b>Glossary Term</b>	<b>Definition</b>
Patient Privacy Policy Identifier	A Patient Privacy Policy Domain-assigned globally unique identifier that identifies the Patient Privacy Policy.
Patient Privacy Policy Domain	The domain for which a Patient Privacy Policy applies. When using XDS this would likely be equivalent to the XDS Affinity Domain.

265

## Volume 1 – Profiles

### Copyright Licenses

*Add the following to the IHE Technical Frameworks General Introduction Copyright section:*

NA

270 **Domain-specific additions**

NA


*Add Section 43*

275 **43 Advanced Patient Privacy Consents (APPC) Profile**

*Advanced Patient Privacy Consents* is a content profile that describes the semantics necessary to enable patient consent(s) to be captured, managed, and communicated between systems and organizations. This profile enables the capturing of consent(s) that cannot be adequately expressed using the Basic Patient Privacy Consents (BPPC) Profile.

280 **43.1 APPC Actors, Transactions, and Content Modules**

A product implementation using this profile must group actors from this profile with actors from a workflow or transport profile to be functional. See Section 43.6.



**Figure 43.1-1: APPC Actor Diagram**

290 Table 43.1-1 lists the content module(s) defined in the APPC Profile. To claim support with this profile, an actor shall support all required content modules (labeled “R”) and may support optional content modules (labeled “O”).

**Table 43.1-1: APPC Profile - Actors and Content Modules**

Actors	Content Modules	Optionality	Reference
Content Creator	Advanced Patient Privacy Consents Content Module	R	ITI TF-3: 5.6.1
Content Consumer	Advanced Patient Privacy Consents Content Module	R	ITI TF-3: 5.6.1

**43.1.1 Actor Descriptions and Actor Profile Requirements**

295 See PCC TF-1: Appendix A.

**43.2 APPC Actor Options**

Options that may be selected for each actor in this profile are listed in Table 43.2-1.

**Table 43.2-1: APPC - Actors and Options**

Actor	Option Name	Reference
Content Creator	No options defined	--
Content Consumer	View Option <sup>Note 1</sup>	Section 43.2.1
	Structured Policy Processing Option <sup>Note 1</sup>	Section 43.2.2

300 Note 1: Content Consumer shall implement at least one of View Option or Structured Policy Processing Option

### 43.2.1 View Option

The requirements for the View Option defined in PCC TF-2: 3.1.1 apply.

### 43.2.2 Structured Policy Processing Option

305 The Content Consumer that supports the Structured Policy Processing Option shall be able to process and interpret the structured policy contained in the APPC document. The option does not require the ability to enforce the rules contained in the structured policy.

## 43.3 APPC Required Actor Groupings

310 An actor from this profile (Column 1) shall implement all of the required transactions and/or content modules in this profile *in addition to* all of the transactions required for the grouped actor (Column 2).

Section 43.5 describes some optional groupings that may be of interest for security considerations and Section 43.6 describes some optional groupings in other related profiles.

**Table 43.3-1: APPC - Required Actor Groupings**

APPC Actor	Actor to be grouped with	Reference	Content Bindings Reference
Content Creator	none	--	--
Content Consumer	none	--	--

315

## 43.4 APPC Overview

The Advanced Patient Privacy Consents (APPC) Profile defines a structural representation of a patient-specific Privacy Policy. The Privacy Policy is considered patient-specific because it includes individualized parts based on the patient’s choices.

320 The content of a Privacy Consent Document is designed to allow an unspecified enforcement mechanism, potentially within an existing access control system, to use the structured policy

representation contained within the consent document to automatically determine and enforce those policies. Such an enforcement mechanism could collect and organize the structured policies to allow for efficient access decisions and enforcement.

325 **43.4.1 Concepts**

Healthcare providers utilize many different sets of data to carry out treatment, billing, and other related operations. This information may include patient demographics, contacts, insurance information, dietary requirements, general clinical information, and sensitive clinical information. This information may be published as independent documents, e.g., by means of the Document Sharing profiles. When using these profiles, each document has a clearly defined set of metadata attributes including coded values denoting the document type, the medical specialty involved, and one or more sensitivity labels (i.e., confidentialityCodes). Healthcare providers also have attributes, such as a functional role, the organization that they work for, which Affinity Domain they belong to, etc.; the Cross-Enterprise User Assertion (XUA) Profile defines one set of such attributes.

330 This profile enables attribute-based security at the document level using the Document Sharing metadata. Documents and accessing providers each have a set of attributes that are clearly defined when using Document Sharing profiles and XUA. Attribute-based security arrives at an access decision (i.e., whether a specific user is authorized to access a specific document) by using a set of rules that compare attributes to each other or against value constraints. To understand attribute-based security conceptually, the specific values, and who determines them, is not critical.

340 Different healthcare providers will have different needs to access these documents. For example, administrators may need to be able to access patient demographics, billing and contact documents. Dietary staff will need access to the dietary documents but would not need access to insurance documents. Patients' assigned doctors will need access to all clinical documents, whereas other providers from the same facility will need access to fewer clinical documents. These statements form one basic Patient Privacy Policy. The policy can be expressed as a set of access rules in an attribute-based security system. Note that such a policy contains nothing that is specific to a particular patient, and only consists of general rules.

350 IHE Document Sharing profiles allow for the publication and use of clinical documents associated with a patient. Privacy Consent is an important attribute of Document Sharing. The IHE Basic Patient Privacy Consents (BPPC) Profile allows the patient to choose from a set of predefined Patient Privacy Policies, without modifications. The APPC Profile allows a Patient Privacy Policy Domain (e.g., an XDS Affinity Domain) to have a number of Patient Privacy Policies that can be individualized and customized.

360 This profile allows Patient Privacy Policy Domains to give patients choices that are more granular by creating access rules that add constraints on top of the rules defined in an underlying Patient Privacy Policy. A patient may not want to give all physicians access to her clinical documents and may therefore limit the Patient Privacy Policies to only apply to a specific

healthcare provider organization (see Section 43.4.2.1) or to a specific episode of care (see Section 43.4.2.2). The patient-specific access rules are transmitted in a structured policy as a part of the consent document.

365 The Patient Privacy Policy Domain determines the available policy customizations. For example, one particular domain may only support blocking of (otherwise permitted) document access to specific care providers, while another domain may allow specific care providers access to certain (otherwise blocked) documents from a specific date range.

370 Neither staff members that digitize paper consent forms, nor patients using a portal to fill out a digital consent form, can be expected to have the knowledge or training to write a consent document with a structured policy from scratch. Therefore, the Patient Privacy Policy Domain must determine a set of foundational, re-usable Patient Privacy Policies defining access patterns (e.g., “full access”, “summaries only”), and clearly define the ways the patient (or other participants) can further make them specific to the patient’s circumstances (e.g., by adding which healthcare provider organization it applies to, by limiting it to documents related to a particular episode of care). When designing the foundational Patient Privacy Policies and the degree of patient-specific adjustments, the Patient Privacy Policy Domain must take many factors into account: the applicable legal framework, medical ethics, the types of data exchanged, the characteristics of the patient population (e.g., age, level of utilization of healthcare services), the capabilities of the IT systems involved, and the exchange participants’ existing access management policies and procedures. Additional factors may be present. Patient Privacy Policy Domains may look to national or regional bodies to assist them in identifying and addressing all relevant factors.

385 A foundational Patient Privacy Policy should identify what the acceptable use and re-disclosure uses are, which functional roles may access which document, and under which conditions. Other representations may exist, e.g., a “patient-friendly” explanation. A unique Privacy Policy Identifier identifies each foundational Patient Privacy Policy. The Patient Privacy Policy Domain has one set of Privacy Policy Identifiers.

390 Along with the normative text, there might be a machine-readable, structured representation of the foundational Patient Privacy Policy, which can be combined with the machine-readable, structured representation of the patient-specific constraints that are included in the Privacy Consent Documents defined in this profile. Combining them enables automatic enforcement of the patient’s privacy choices. How to combine these different sets of access rules is not in scope for this profile.

395 Combining Patient Privacy Policies from different Patient Privacy Policy Domains might be difficult. An exchange of foundational Patient Privacy Policies using a structured policy format between different Patient Privacy Policy Domains might allow automatic enforcement of Privacy Consent Documents from other Patient Privacy Policy Domains, but this is not part of the APPC Profile.

### 43.4.2 Use Cases

400 The following use cases illustrate the capabilities enabled by this profile. They are not meant to be an exhaustive list of supported patient consent / access control schemes, nor are they intended to imply any particular implementation. The use cases all share a level of complexity that would be challenging to implement using BPPC and therefore are a better fit for this profile.

#### 43.4.2.1 Use Case #1: Facility-specific Disclosure

405 In this use case, the patient grants access to his data to the staff of a specific facility. The extent of access and any accompanying restrictions are condensed into an access patterns that the patient selects for this facility.

##### 43.4.2.1.1 Facility-specific Disclosure Use Case Description

###### Pre-Condition:

410 This use case takes place in an opt-in XDS Affinity Domain, where access to PHI is only granted if the patient explicitly agreed to share documents.

The XDS Affinity Domain – acting as the Patient Privacy Policy Domain – has defined three foundational Patient Privacy Policies, which may be referenced in a Privacy Consent Document. The XDS Affinity Domain consists of 50 separate facilities.

415 The facilities providing care for the patient (a hospital and a post-surgical care facility) can exchange data via an HIE using a common patient ID and these facilities are listed in the HIE’s Healthcare Provider Directory.

###### Main Flow:

420 A patient visits a hospital because he needs a hip replacement. After the procedure, the hospital wants to arrange post-discharge care at another facility. The hospital uploaded all relevant data regarding the procedure to its HIE. A staff member asks the patient to sign a consent form that authorizes the HIE to grant access to the patient’s health data to the target facility. The patient has a choice between three access patterns, which are listed on the form: “summary-only” access, “general” access, and “full” access. The patient selects “general” access, which includes most  
425 notes, labs and images, but excludes particularly sensitive documents (e.g., psychiatric evaluations). The patient signs the form.

The staff member selects the patient in the EHR, searches for the post-surgical care facility in the connected Healthcare Provider Directory, selects the facility, and then selects the access pattern (“general”). The EHR creates a Privacy Consent Document and transmits it to the central XDS  
430 Document Repository in the HIE. After discharge from the hospital, the patient visits the post-surgical care facility. The HIE’s enforcement mechanism (acting as an APPC Content Consumer with the Structured Policy Processing Option) uses the structured and coded policy from the consent document to decide to grant access to the longitudinal patient record for users from the post-surgical care facility.


435 **Post-Condition:**

The longitudinal patient record in the HIE contains a consent document.

The doctors and care providers in the post-surgical care facility can access the patient’s longitudinal record in the HIE.

440 The doctors and care providers in facilities not involved in the patient’s care cannot access the patient’s longitudinal record in the HIE.

**43.4.2.1.2 Facility-specific Disclosure Process Flow**



445 **Figure 43.4.2.1.2-1: Facility-specific Disclosure Process Flow in APPC Profile**

**43.4.2.2 Use Case #2: Consent for an Episode of Care**

In this use case, the patient allows a care team consisting of healthcare providers from multiple organizations to exchange data related to a specific episode of care. All care team members have the same level of access.

450 The detailed access rules for the care team members are defined independently of the patient’s consent by the HIE.



#### 43.4.2.2.1 Consent for an Episode of Care Use Case Description

##### **Pre-Conditions:**

455 This use case takes place in an opt-in XDS Affinity Domain, where all patient data is organized as episodes of care. The episode of care is summarized by a diagnostic code and always has an (expected) end date.

The patient is identified using a common patient ID.

The participating providers and organizations are listed in the HIE's Healthcare Provider Directory.

##### 460 **Main Flow:**

A patient has completed an inpatient treatment for depression at a mental health treatment center. A staff member of the center recommends a care team consisting of a psychiatrist, the patient's primary care physician, and an occupational therapist. The staff member initiates a new episode of care in her information system to allow the care team to exchange all relevant documentation (i.e., documents regarding the inpatient treatment, psychiatric evaluations, occupational therapy progress notes, and intervention plans).

470 In the information system, the staff member selects the patient, then the diagnostic code that best summarizes the episode of care and enters the expected duration of the episode. She searches in the provider directory to find the care team members and adds them in her information system to the episode of care. The system prints out a consent form containing this data. The patient signs it and the nurse confirms the signature in her system.

475 The treatment center's system creates an XDS Folder representing the episode of care and a Privacy Consent Document referencing the Folder. The system sends these objects via its XDS Document Source to the central XDS Document Repository. When a care team member tries to access the episode of care, the HIE's security system (acting as an APPC Content Consumer with the Structured Policy Processing Option) extracts the structured and coded policy representation and makes an access decision.


##### **Post-Condition:**

The longitudinal patient record in the HIE contains the consent document.

480 The care team can upload and access any documents in the record that are linked to an XDS Folder that has the episode's diagnostic code in its folder codeList.

Other healthcare providers do not have access to the documents in the record that are linked to an XDS Folder that has the episode's diagnostic code in its folder codeList.

### 43.4.2.2.2 Consent for an Episode of Care Process Flow



485

Figure 43.4.2.2.2-1: Consent for an Episode of Care Process Flow in APPC Profile

### 43.4.2.3 Use Case #3: Consent to Collect from a Specific Service Delivery Location

490 This use case describes a situation where the patient wishes to provide consent for an organization to collect information from one or more specific provider locations for multiple purposes.

#### 43.4.2.3.1 Consent to Collect from a Specific Service Delivery Location Use Case Description

##### Pre-Condition:

495 This use case takes place in an opt-in XDS Affinity Domain, where collection of protected health information is only granted if the patient explicitly agreed to it. The patient has the right to specify which providers and service delivery locations can be included in that consent.

A clinic has an EMR system that has the capability to transmit clinical documents to an XDS Affinity Domain.

500 The clinic and the organization managing the HIE have agreements in place which allow the exchange of clinical information for certain purposes specified within the patient's signed consent document.

**Main Flow:**

505 The patient goes to a Family Practice Clinic for his annual checkup and is provided with a pamphlet describing the associated HIE and the potential advantages of having his healthcare information readily available to other healthcare providers in his area should the need arise.

510 After reading the material and discussing the advantages and potential risks with his physician, the patient decides to allow his records from the Family Practice Clinic to be registered with the HIE. He is presented with, and signs, an electronic consent form indicating that documents from the specific facility are permitted to be shared with the HIE.

515 The receptionist saves the signed consent form in the clinic’s EMR system and has the EMR transmit the document to the HIE for processing before sending the patient’s clinical records that were a result of today’s appointment. The consent document is stored in the HIE’s XDS Document Repository and is used by the HIE’s security system to confirm that the patient’s clinical documents may be collected.

**Post-Condition:**

The longitudinal patient record in the HIE contains a consent document.

The longitudinal patient record in the HIE contains the documents resulting from the appointment in the Family Practice Clinic.

520 **43.4.2.3.2 Consent to Collect from a Specific Service Delivery Location Process Flow**




Figure 43.4.2.3.2-1: Consent to Collect from a Specific Service Delivery Location Process Flow in APPC Profile

525

#### 43.4.2.4 Use Case #4: Withhold Consent for Information Related to a Specific Order

This use case describes a situation where the patient wishes to restrict the disclosure of the fact that a specific order was made as well as any information resulting from that order.

##### 530 43.4.2.4.1 Withhold Consent to Disclose Information Related to a Specific Order Use Case Description

**Pre-Condition:**

The patient lives in a jurisdiction that has a central lab information repository where all lab orders and results are kept.

535 The jurisdiction uses an implied consent model for the provision of care, which means that the document would be visible by default.

**Main Flow:**

540 The patient goes to his primary care provider for screening for sexually transmitted diseases. He is a nurse in a local hospital and is concerned that his colleagues may have access to the order and test results.

545 The primary care provider would like to order a battery of tests in order to confirm a diagnosis. The patient indicates that he would like to withhold his consent for the disclosure of the battery order and the subsequent results. After some discussion, the provider enters the order into her lab’s online order form and indicates that the patient has withheld consent for disclosure. This withholding of consent does not affect potential disclosure for public health reasons.

The lab information repository generates a lab order, and a consent document specifying that the patient wishes to deny access to the order, except to the ordering physician.


550 Later, a colleague attempts to view the patient’s record and issues a request to list all lab records. Because of the information in the consent document, the lab information repository eliminates the order and result records from the colleague’s search results.

**Post-Condition:**

The ordering physician has access to the lab order and result.

Other healthcare providers do not have access to the specific lab order and result but may still have access to the patient’s other lab orders and results.

555 **43.4.2.4.2 Withhold Consent for Information Related to a Specific Order Process Flow**



**Figure 43.4.2.4.2-1: Withhold Consent for Information Related to a Specific Order Process Flow in APPC Profile**

560

#### **43.4.2.5 Use Case #5: Withhold Consent to Disclose to a Specific Provider Organization**

This use case details a scenario where the patient does not wish any of her health information disclosed to a particular organization.

##### **565 43.4.2.5.1 Withhold Consent to Disclose to a Specific Provider Organization Use Case Description**

###### **Pre-Condition:**

The jurisdiction uses an implied consent model for the provision of care, which means that the document would be visible by default.

570 The jurisdiction uses technical and governance mechanisms outside of the scope of this profile to ensure that the operators of the connected systems respect the patient’s choices reflected in the consent documents.

###### **Main Flow:**

575 The patient is a nurse at a local hospital. He has been diagnosed with an STD and is beginning treatment at a family practice clinic. The patient previously withheld his consent so that nobody but the ordering physician would be able to see the initial lab order and results. Now that he is beginning treatment, he does not wish to disclose any of his health information to the local hospital that he works at.

580 There is a jurisdictional consent repository (maintaining only consents) where the patient lives, so he calls the consent service desk to have his records blocked when accessed from the local hospital. After the client service representative establishes the patient’s identity, she creates a new consent document, and saves it to the repository.

585 Later, a colleague tries to view the patient’s records and issues a request in the hospital’s EMR to list all of the patient’s documents in the connected HIE. The EMR checks the jurisdictional consent repository before querying the HIE and processes the returned consent document. The EMR does not send the request to the HIE, since it is able to determine that access should be blocked for the local hospital.


###### **Post-Condition:**

The jurisdictional consent repository contains a consent document.

590 Healthcare providers in the local hospital do not have access to the patient’s documents in the HIE.

Other healthcare providers still have access to the patient’s documents in the HIE.

### 43.4.2.5.2 Withhold Consent to Disclose to a Specific Provider Organization Process Flow



595

**Figure 43.4.2.5.2-1: Withhold Consent to Disclose to a Specific Provider Organization Process Flow in APPC Profile**

### 43.4.2.6 Use Case #6: Withhold Consent to Disclose a Specific Document

600 This use case details a scenario where the patient does not wish that a specific document be disclosed to any healthcare provider.

#### 43.4.2.6.1 Withhold Consent to Disclose a Specific Document Use Case Description

##### Pre-Condition:

605 The XDS Affinity Domain uses an implied consent model for the provision of care, which means that all documents would be accessible by default.

The patient has access to a patient portal with the ability to list and display all documents available in his longitudinal patient record.

610 In this jurisdiction, the patient has the right to deny access to any individual document in his longitudinal patient record. According to this jurisdiction's rules, there must be no indication in the record if the patient has decided to deny access to any documents.

##### Main Flow:

615 The patient has undergone a drug screening and the resulting document has been added automatically to his longitudinal patient record by the lab. He does not want this document to be accessible by his healthcare providers.

The patient logs into the patient portal and finds the drug screening result document. He selects the option to “hide” this document. The patient portal presents the potential risks of hiding information from healthcare providers. The patient acknowledges the warning and confirms that the document should be hidden.

620 The patient portal creates a Privacy Consent Document. The consent includes a structured policy that denies access to this document and to the consent document itself to anybody except the patient. The patient portal sends the document to the HIE using the Mobile access to Health Documents (MHD) Profile. The HIE extracts the structured policy and adjusts the access rights accordingly.

625 A healthcare provider accesses the HIE through his EMR. The provider sees the patient’s other clinical documents but does not see that there is a drug screening result document or that a document has been hidden.

**Post-Condition:**


The longitudinal patient record in the HIE contains a consent document.

630 Healthcare providers do not have access to the drug screening result document in the HIE.

Healthcare providers do not have access to the consent document in the HIE.

The patient has access to the drug screening result document and the consent document in the HIE using the patient portal.

**43.4.2.6.2 Withhold Consent to Disclose a Specific Document Process Flow**



635

**Figure 43.4.2.6.2-1: Withhold Consent to Disclose to Specific Document Process Flow in APPC Profile**



### 43.5 APPC Privacy and Security Considerations

640 Like patients’ clinical documents, consent documents are also governed by privacy policies. The content of a Privacy Consent Document may itself contain sensitive information. For example, a terminally ill patient may decide that his prognosis should not be shared with his family members, but that other information may be. Sharing the Privacy Consent Document with family members would potentially inform them of a negative prognosis. Thus, the confidentialityCode  
645 placed on Privacy Consent Documents must be appropriately assigned. Another solution is to include access rules in the Privacy Consent Document that specifically regulate access to the consent document itself (see Section 43.4.2.6 for an example).

The machine processing of structured policies within a healthcare environment has different considerations and risks than interpreting similar structured policies within other non-treatment  
650 environments. Policies must be crafted to prevent inappropriate disclosure while enabling appropriate access to critical healthcare information (e.g., severe allergies). The Patient Privacy Policy Domain should take care in designing the policies for its access control system including appropriate “break-glass” policies. Governance of privacy policies is concerned with instances of multiple conflicting policies and the ability to identify and retrieve all applicable policies.

655 One mitigation strategy that is often adopted in healthcare is to provide accountability through audit controls. Healthcare providers are trusted not to abuse their ability to access patient’s private information, but that is backed up by a policy of monitoring provider access to detect if abuse has occurred. This strategy reduces the risk of death or serious injury due to lack of access to critical healthcare information, at the increased risk of disclosure of private information. The  
660 Audit Trail and Node Authentication (ATNA) Integration Profile, which is mandated for actors in IHE Document Sharing and related profiles, describes a framework for such audit logs.

Quality identification, authentication, and authorization governance are critical components of privacy and security. A failure to provide access, or an accidental disclosure, may be caused by inaccurate document metadata, e.g., mislabeled documents, and by inaccurate Privacy Consent  
665 Documents, e.g., inserting the wrong facility identifier in a structured policy. The XDS Affinity Domain can mitigate these risks by establishing a quality control system. This includes establishing well-documented processes for manually-selected metadata and careful review of metadata automatically mapped from other formats.

### 43.6 APPC Cross Profile Considerations

670 A Content Creator or Content Consumer may be grouped with appropriate actors from document sharing profiles such as XDS, XDM, or XDR to exchange the Privacy Consent Document.

The Document Sharing metadata has specific relationships or dependencies (which we call bindings) to the content of the Advanced Patient Privacy Consent document described in this content profile. ITI TF-3: 5.6.1.2.2 defines the bindings to use when grouping the Content  
675 Creator of this profile with actors from document sharing profiles such as XDS, XDM, or XDR.

680 The APPC Profile and the BPPC Profile can both be used to support digital consent documents. Generally, any consent document that can be expressed via BPPC can also be expressed via APPC. Whether APPC is the best approach for a particular Patient Privacy Policy Domain depends on the complexity of the Patient Privacy Policies and the capabilities of the systems involved in the exchange. Whereas APPC allows for individualized consents that further constrain generally applicable policies, BPPC only allows a choice from a set of predefined Patient Privacy Policies. Further guidance regarding how to design Patient Privacy Policies and how to choose between APPC and BPPC can be found in Appendix P.

## Appendices

- 685 *This section is left blank. It is a placeholder for an updated Appendix P, which will be created by CP-ITI-948. The appendix is aiming to assist readers in creating privacy policies and in deciding when to use APPC or BPPC.*

## **Volume 2 – Transactions**

No updates to Volume 2.

690

## **Volume 3 – Content Modules**

## 5 IHE Content Specifications

*Add to Section 5 IHE Content Specifications*

### 5.6 Advanced Patient Privacy Consents Content Module

This section defines the Privacy Consent Document.

#### 695 5.6.1 References

All standards, which are referenced in this document, are listed below with their common abbreviation, full title, and link to the standard.

**Table 5.6.1-1: Advanced Patient Privacy Consents - Referenced Standards**

Abbreviation	Title	URL
XACML2	eXtensible Access Control Markup Language (XACML) Version 2.0	<a href="#">XACML Core 2.0</a>
HL7ADTS	HL7v3 Abstract Data Type Specification - ANSI/HL7 V3 DT, R1-2004 3/19/2012	<a href="#">HL7v3 ADTS</a>

#### 700 5.6.2 Privacy Consent Document Specification

##### 5.6.2.1 Content Specification

The Privacy Consent Document shall be an XML document, adhering to the specifications found in [XACML2]. Its purpose is to express unambiguously the access granted by the patient to a provider, group of providers or any other participant in a Document Sharing environment. It specifically focuses on expressing authorizations based on IHE Document Sharing Metadata and transactions, as well as attributes in the Provide X-User Assertion [ITI-40] transaction in the Cross-Enterprise User Assertion (XUA) Profile. It can also be used for expressing authorizations based on other attributes, but this requires agreement on those attributes between Content Creators and the enforcement system, possibly established by national or regional regulators or through national extensions.

Attributes that the Content Creator may use in a Privacy Consent Document are defined in sections below:

- IHE XUA attributes are defined in Section 5.6.2.1.4
- General IHE Document Sharing attributes are defined in Section 5.6.2.1.5
- 715 • DocumentEntry attributes are defined in Section 5.6.2.1.5.2
- Folder attributes are defined in Section 5.6.2.1.5.3
- SubmissionSet attributes are defined in Section 5.6.2.1.5.4

An informative schema is available. See ITI TF-2x: Appendix W.

### 5.6.2.1.1 Policy Structure

720 The Privacy Consent Document shall contain exactly one `PolicySet` root element. As defined in [XACML2], it may contain other `PolicySet` elements as child elements of the root. The `PolicySet` root element may also contain `Policy` child elements. The `PolicySetId` attribute of the `PolicySet` root element is known as the Root Policy Set ID and must be a URN-encoded globally unique identifier as defined by ITI TF-2x: Appendix B.

725 The `PolicySet` root element may contain references to other `PolicySet` or `Policy` elements, using the `PolicySetIdReference` or the `PolicyIdReference` elements respectively. This allows the Patient Privacy Policy Domain to define foundational Patient Privacy Policies, which are applied to specific individuals and situations by the Privacy Consent Document. E.g., a referenced foundational Patient Privacy Policy defines what kind of access a healthcare provider receives; the Privacy Consent Document applies this to one specific provider, patient, and purpose of use. How external references are resolved is out of scope for this profile.

730 The `PolicySet` root element shall contain at least one `//Target/Resources/Resource/ResourceMatch/ResourceAttributeDesignator` element with `AttributeId urn:ihe:iti:ser:2016:patient-id`, which restricts its applicability to one or more patient IDs belonging to one patient (see Section 5.6.2.1.5.1.5). When using IHE Document Sharing profiles, the patient ID in the Privacy Consent Document should be identical to the patient ID in the Document Sharing metadata. Note that patient merge events can change the patient ID in the Document Sharing metadata and that this may necessitate changes of the patient ID in the structured policy as well.

### 740 5.6.2.1.1.1 Human Readable Representation

The `PolicySet` root element shall contain a `Description` child element. This `Description` element shall contain a plain text description (i.e., no markup) of the contents of the Privacy Consent Document. It may hold information on who signed the consent form, when it was signed and what person or organization is responsible for this document.

745 Other elements in the Privacy Consent Document may contain additional `Description` elements that explain the relevant aspects of that `PolicySet`, `Policy`, or `Rule`.

The `Description` element has a limited ability to carry human readable representation. Therefore, Content Creators may create a separate document containing the human readable representation of the Privacy Consent Document. The document may be a BPPC consent acknowledgment document (see ITI TF-3: 5.1), a PDF (e.g., following the XDS-SD Profile – see ITI TF-3: 5.2), or any other appropriate format. When transmitting such an additional representation using IHE Document Sharing profiles, the Content Creator shall register the human readable representation as a separate document entry and add a transformation (XFRM) association linking the Privacy Consent Document and the human readable document. The XDS Affinity Domain may decide whether the Privacy Consent Document is considered a transformation of the human readable

750

755

document or whether the human readable document is considered a transformation of the Privacy Consent Document (i.e., the direction of the association between the two).

When the human readable representation is a BPPC consent acknowledgment document, the Root Policy Set ID of the Privacy Consent Document and the BPPC Patient Privacy Policy Identifier shall be identical.

760

### 5.6.2.1.1.2 Example Document

765

```
<?xml version="1.0" encoding="UTF-8"?>
<PolicySet PolicySetId="urn:uuid:e3585197-9e3d-4ca3-9583-4540a3a5b64b"
  PolicyCombiningAlgId=
    "urn:oasis:names:tc:xacml:1.0:policy-combining-algorithm:deny-overrides"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:hl7="urn:hl7-org:v3"
  xmlns="urn:oasis:names:tc:xacml:2.0:policy:schema:os"
  xsi:schemaLocation="urn:oasis:names:tc:xacml:2.0:policy:schema:os ihe-appc-
770 xacml-combined-schema-1.0.xsd">
  <Description>The patient agrees to grant access to the identified
  facility. The extent of access is defined by the referenced policy.
  </Description>
  <Target>
775   <Subjects>
     <Subject>
       <SubjectMatch
  MatchId="urn:oasis:names:tc:xacml:1.0:function:anyURI-equal">
         <AttributeValue
780   DataType="http://www.w3.org/2001/XMLSchema#anyURI">
           urn:oid:2.999.2.1.1.35
         </AttributeValue>
         <SubjectAttributeDesignator
  DataType="http://www.w3.org/2001/XMLSchema#anyURI"
785   AttributeId="urn:oasis:names:tc:xspa:1.0:subject:organization-id" />
         </SubjectMatch>
       </Subject>
     </Subjects>
     <Resources>
790   <Resource>
       <ResourceMatch MatchId="urn:hl7-org:v3:function:II-equal">
         <AttributeValue DataType="urn:hl7-org:v3#II">
           <hl7:InstanceIdentifier root="2.999.1.1.1"
795   extension="78901234" />
         </AttributeValue>
         <ResourceAttributeDesignator DataType="urn:hl7-org:v3#II"
           AttributeId="urn:ihe:iti:ser:2016:patient-id" />
         </ResourceMatch>
       </Resource>
     </Resources>
800   </Target>
  <PolicySetIdReference>
    urn:example:policy:extensive-access
```



805       </PolicySetIdReference>  
      </PolicySet>

### 5.6.2.1.2 Data Types

810       The Privacy Consent Document relies on data types derived from HL7v3 (see [HL7ADTS] Section 2.9 and 2.17) to represent complex data types such as coded values and instance identifiers. These data types utilize the XACML extensibility described in chapter 8 of [XACML2]. If the name of the XML attribute or element matches a property name in the HL7v3 Data Types Abstract Specification then the semantics of the content will be as described in the HL7v3 Data Types Abstract Specification, otherwise the narrative will explain the use of the attribute or element.

#### 815   **Coded Values Data Type**

Data type URI: urn:hl7-org:v3#CV

Specification:

820       A CV shall have the XML element `codedValue` with the XML attributes `code` and `codeSystem`. `code` may be any string. `codeSystem` shall be an OID. A CV may also have the XML attributes `codeSystemName`, `codeSystemVersion`, `displayName` and the XML child element `originalText`. `codeSystemName`, `codeSystemVersion`, and `displayName` may be any string.

Example:

```
<CodedValue code="1" codeSystem="1.0.14265.1" />
```

#### 825   **Instance Identifier Data Type**

Data type URI: urn:hl7-org:v3#II

830       An Instance Identifier shall have the XML element `InstanceIdentifier` with the XML attribute `root` and may have the XML attribute `extension`. `extension` may be any string. `root` shall be an OID. An Instance Identifier may also have the XML attribute `assigningAuthorityName` and `displayable`. `assigningAuthorityName` may be any string. `displayable` must be either `true` or `false` if it exists.

Example:

```
<InstanceIdentifier extension="11231" root="2.16.840.1.113883.19" />
```

### 5.6.2.1.3 Functions

835       The use of HL7v3-derived data types in Privacy Consent Documents necessitates the use of custom functions to compare attributes with those data types. These functions utilize the XACML extensibility described in chapter 8 of [XACML2].

### Coded Value Comparison Function

Function URI: urn:hl7-org:v3:function:CV-equal

840 This function shall take two arguments of data-type urn:hl7-org:v3#CV and SHALL return an http://www.w3.org/2001/XMLSchema#boolean. The function shall return True if and only if the code attribute of both of its arguments are equal according to the function urn:oasis:names:tc:xacml:1.0:function:string-equal AND the codeSystem attribute of both of its arguments are equal according to the function urn:oasis:names:tc:xacml:1.0:function:string-equal. Otherwise, it shall return False.

### Instance Identifier Comparison Function

Function URI: urn:hl7-org:v3:function:II-equal

850 This function shall take two arguments of data-type urn:hl7-org:v3#II and shall return an http://www.w3.org/2001/XMLSchema#boolean. The function shall return True if:

- the extension attribute is empty and the root attribute of both of its arguments are equal according to the function urn:oasis:names:tc:xacml:1.0:function:string-equal; or,
- the extension attribute of both of its arguments are equal according to the function urn:oasis:names:tc:xacml:1.0:function:string-equal, and the root attribute of both of its arguments are equal according to the function urn:oasis:names:tc:xacml:1.0:function:string-equal.

855 Otherwise, it shall return False.

## 5.6.2.1.4 Attribute Definitions – Subject

### 860 5.6.2.1.4.1 User ID

<b>IHE XUA Definition</b>	ITI TF-2b: 3.40.4.1.2 as "Subject" - "logical identifier of the principal performing the original service request"
<b>SAML Attribute Name</b>	not an attribute in SAML, but communicated in <Subject>/<NameID>
<b>SAML Example</b>	<pre>&lt;saml:Subject&gt;   &lt;saml:NameID&gt;user1&lt;/saml:NameID&gt;   &lt;saml:SubjectConfirmation     Method="urn:oasis:names:tc:SAML:2.0:cm:bearer"/&gt; &lt;/saml:Subject&gt;</pre>
<b>XACML Target Section</b>	subject

<b>XACML Attribute ID</b>	urn:oasis:names:tc:xacml:1.0:subject:subject-id
<b>XACML Data Type</b>	http://www.w3.org/2001/XMLSchema#string
<b>XACML Attribute Value Content</b>	No restrictions
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId="urn:oasis:names:tc:xacml:1.0:subject:subject-id" DataType="http://www.w3.org/2001/XMLSchema#string"&gt;   &lt;AttributeValue&gt;user1&lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

#### 5.6.2.1.4.2 User Organization

<b>IHE XUA Definition</b>	ITI TF-2b: 3.40.4.1.2 as "Subject Organization" - "plain text description of the organization"
<b>SAML Attribute Name</b>	urn:oasis:names:tc:xspa:1.0:subject:organization
<b>SAML Example</b>	<pre>&lt;saml:Attribute Name="urn:oasis:names:tc:xspa:1.0:subject:organization"&gt;   &lt;saml:AttributeValue&gt;Family Medical Clinic   &lt;/saml:AttributeValue&gt; &lt;/saml:Attribute&gt;</pre>
<b>XACML Target Section</b>	subject
<b>XACML Attribute ID</b>	urn:oasis:names:tc:xspa:1.0:subject:organization
<b>XACML Data Type</b>	http://www.w3.org/2001/XMLSchema#string
<b>XACML Attribute Value Content</b>	No restrictions
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId="urn:oasis:names:tc:xspa:1.0:subject:organization" DataType="http://www.w3.org/2001/XMLSchema#string"&gt;   &lt;AttributeValue&gt;Family Medical Clinic&lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

#### 5.6.2.1.4.3 User Organization ID

<b>IHE XUA Definition</b>	ITI TF-2b: 3.40.4.1.2 as "Subject Organization ID" - "a unique identifier for the organization that the user is representing in performing this transaction"
<b>SAML Attribute Name</b>	urn:oasis:names:tc:xspa:1.0:subject:organization-id
<b>SAML Example</b>	<pre>&lt;saml:Attribute Name="urn:oasis:names:tc:xspa:1.0:subject:organization-id"&gt;   &lt;saml:AttributeValue&gt;http://familymedicalclinic.org &lt;/saml:AttributeValue&gt; &lt;/saml:Attribute&gt;</pre>
<b>XACML Target Section</b>	subject
<b>XACML Attribute ID</b>	urn:oasis:names:tc:xspa:1.0:subject:organization-id
<b>XACML Data Type</b>	http://www.w3.org/2001/XMLSchema#anyURI
<b>XACML Attribute Value Content</b>	The organization ID shall be one of: a) Object Identifier (OID), using the urn format (i.e., "urn:oid:" followed by the OID); b) a URL assigned to that organization.
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId= "urn:oasis:names:tc:xspa:1.0:subject:organization-id" DataType="http://www.w3.org/2001/XMLSchema#anyURI"&gt;   &lt;AttributeValue&gt;http://familymedicalclinic.org &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

#### 5.6.2.1.4.4 User Home Community ID

<b>IHE XUA Definition</b>	ITI TF-2b: 3.40.4.1.2 as "Home Community ID"
<b>SAML Attribute Name</b>	urn:ihe:iti:xca:2010:homeCommunityId
<b>SAML Example</b>	<pre>&lt;saml:Attribute Name="urn:ihe:iti:xca:2010:homeCommunityId"&gt;   &lt;saml:AttributeValue&gt;     urn:oid:2.16.840.1.113883.3.190   &lt;/saml:AttributeValue&gt; &lt;/saml:Attribute&gt;</pre>

<b>XACML Target Section</b>	subject
<b>XACML Attribute ID</b>	urn:ihe:iti:xca:2010:homeCommunityId
<b>XACML Data Type</b>	http://www.w3.org/2001/XMLSchema#anyURI
<b>XACML Attribute Value Content</b>	The identifier shall be an Object Identifier (OID), using the urn format ("urn:oid:" followed by the OID)
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId= "urn:ihe:iti:xca:2010:homeCommunityId"   DataType="http://www.w3.org/2001/XMLSchema#anyURI"&gt;   &lt;AttributeValue&gt;     urn:oid:2.16.840.1.113883.3.190   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

#### 5.6.2.1.4.5 National Provider Identifier (NPI)

<b>IHE XUA Definition</b>	ITI TF-2b: 3.40.4.1.2 as "National Provider Identifier"
<b>SAML Attribute Name</b>	urn:oasis:names:tc:xspa:1.0:subject:npi
<b>SAML Example</b>	<pre>&lt;saml:Attribute Name="urn:oasis:names:tc:xspa:1.0:subject:npi"&gt;   &lt;saml:AttributeValue&gt;1234567890&lt;/saml:AttributeValue&gt; &lt;/saml:Attribute&gt;</pre>
<b>XACML Target Section</b>	subject
<b>XACML Attribute ID</b>	urn:oasis:names:tc:xspa:1.0:subject:npi
<b>XACML Data Type</b>	urn:hl7-org:v3#II
<b>XACML Attribute Value Content</b>	The Content Creator shall select an appropriate instance identifier root representing the namespace of the national provider identifier.

<b>XACML Example</b>	<pre>&lt;Attribute   AttributeId="urn:oasis:names:tc:xspa:1.0:subject:npi"   DataType="urn:hl7-org:v3#II"&gt;   &lt;AttributeValue&gt;     &lt;hl7:InstanceIdentifier extension="1234567890"       root="2.16.840.1.113883.4.6" /&gt;   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>
----------------------	--

865 **5.6.2.1.4.6 User Role**

<b>IHE XUA Definition</b>	ITI TF-2b: 3.40.4.1.2.1 as "Subject-Role"
<b>SAML Attribute Name</b>	urn:oasis:names:tc:xacml:2.0:subject:role
<b>SAML Example</b>	<pre>&lt;saml:Attribute   Name="urn:oasis:names:tc:xacml:2.0:subject:role"&gt;   &lt;saml:AttributeValue&gt;     &lt;Role xmlns="urn:hl7-org:v3"       xsi:type="CE" code="46255001"       codeSystem="2.16.840.1.113883.6.96"       codeSystemName="SNOMED_CT"       displayName="Pharmacist"/&gt;   &lt;/saml:AttributeValue&gt; &lt;/saml:Attribute&gt;</pre>
<b>XACML Target Section</b>	subject
<b>XACML Attribute ID</b>	urn:oasis:names:tc:xacml:2.0:subject:role
<b>XACML Data Type</b>	urn:hl7-org:v3#CV
<b>XACML Attribute Value Content</b>	No restrictions
<b>XACML Example</b>	<pre>&lt;Attribute   AttributeId="urn:oasis:names:tc:xacml:2.0:subject:role"   DataType="urn:hl7-org:v3#CV"&gt;   &lt;AttributeValue&gt;     &lt;hl7:CodedValue code="46255001"       codeSystem="2.16.840.1.113883.6.96" /&gt;   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

#### 5.6.2.1.4.7 Purpose Of Use

<b>IHE XUA Definition</b>	ITI TF-2b: 3.40.4.1.2.3 as "PurposeOfUse"
<b>SAML Attribute Name</b>	urn:oasis:names:tc:xspa:1.0:subject:purposeofuse
<b>SAML Example</b>	<pre>&lt;saml:Attribute   name="urn:oasis:names:tc:xspa:1.0:subject:purposeofuse"&gt;   &lt;saml:AttributeValue&gt;     &lt;PurposeOfUse xmlns="urn:hl7-org:v3" xsi:type="CE"       code="12"       codeSystem="1.0.14265.1"       codeSystemName="ISO 14265 Classification of Purposes for processing personal health information"       displayName="Law Enforcement"/&gt;     &lt;/saml:AttributeValue&gt;   &lt;/saml:Attribute&gt;</pre>
<b>XACML Target Section</b>	subject
<b>XACML Attribute ID</b>	urn:oasis:names:tc:xspa:1.0:subject:purposeofuse
<b>XACML Data Type</b>	urn:hl7-org:v3#CV
<b>XACML Attribute Value Content</b>	No restrictions
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId= "urn:oasis:names:tc:xspa:1.0:subject:purposeofuse" DataType="urn:hl7-org:v3#CV"&gt;   &lt;AttributeValue&gt;     &lt;hl7:CodedValue code="12"       codeSystem="1.0.14265.1" /&gt;     &lt;/AttributeValue&gt;   &lt;/Attribute&gt;</pre>

#### 5.6.2.1.4.8 Other Provider Identifier

<b>IHE XUA Definition</b>	ITI TF-2b: 3.40.4.1.2 as "Other Provider Identifier"
<b>SAML Attribute Name</b>	urn:ihe:iti:xua:2017:subject:provider-identifier

<b>SAML Example</b>	<pre>&lt;saml:Attribute   name="urn:ihe:iti:xua:2017:subject:provider-identifier"&gt;   &lt;saml:AttributeValue&gt;     &lt;id xmlns="urn:hl7-org:v3" xsi:type="II"       extension="1234567890" root="2.999.1.2.3.4.5"       assigningAuthorityName="Example Authority"       displayable="true"/&gt;   &lt;/saml:AttributeValue&gt; &lt;/saml:Attribute&gt;&gt;</pre>
<b>XACML Target Section</b>	subject
<b>XACML Attribute ID</b>	urn:ihe:iti:xua:2017:subject:provider-identifier
<b>XACML Data Type</b>	urn:hl7-org:v3#II
<b>XACML Attribute Value Content</b>	No restrictions
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId=   "urn:ihe:iti:xua:2017:subject:provider-identifier"   DataType="urn:hl7-org:v3#II"&gt;   &lt;AttributeValue&gt;     &lt;hl7:InstanceIdentifier extension="123456789012"       root="2.999.1"/&gt;   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

### 5.6.2.1.5 Attribute Definitions – Resources

#### 870 5.6.2.1.5.1 Attribute Definitions – General Document Sharing Attributes

This section describes how to express IHE Document Sharing metadata in XACML for metadata attributes used in multiple resource types (DocumentEntries, Folders, or SubmissionSets).

##### 5.6.2.1.5.1.1 Author Institution ID

<b>IHE Document Sharing Metadata Definition</b>	<p>ITI TF-3: 4.2.3.1.4.1 as "authorInstitution"; this attribute can be used to restrict access based on the authorInstitution identifier.</p> <p>Note that the identifiers might belong to multiple, separate authors. When including both an authorPerson ID and an authorInstitution ID in a policy, policy writers need to take into account that they might belong to different authors in the IHE Document Sharing metadata.</p>
---	---



<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:ihe:iti:appc:2016:author-institution:id
<b>XACML Data Type</b>	urn:hl7-org:v3#II
<b>XACML Attribute Value Content</b>	If XON.10 is an OID, use XON.10 as root with no extension. If XON.10 is not an OID, use XON.6.2 as root and XON.10 as extension
<b>Used in Resource Type</b>	DocumentEntry, SubmissionSet
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId="urn:ihe:iti:appc:2016:author-institution:id" DataType="urn:hl7-org:v3#II"&gt;   &lt;AttributeValue&gt;     &lt;hl7:InstanceIdentifier root="1.2.3.9.1789.45"/&gt;   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

#### 5.6.2.1.5.1.2 Author Person ID

<b>IHE Document Sharing Metadata Definition</b>	<p>ITI TF-3: 4.2.3.1.4.2 as "authorPerson"; this attribute can be used to restrict access based on the authorPerson identifier.</p> <p>Note that the identifiers might belong to multiple, separate authors. When including both an authorPerson ID and an authorInstitution ID in a policy, policy writers need to take into account that they might belong to different authors in the IHE Document Sharing metadata.</p>
<b>XACML Target Section</b>	Resource
<b>XACML Attribute ID</b>	urn:ihe:iti:appc:2016:author-person:id
<b>XACML Data Type</b>	urn:hl7-org:v3#II
<b>XACML Attribute Value Content</b>	If XCN.1 is an OID, use XCN.1 as root with no extension. If XCN.1 is not an OID, use XCN.9.2 as root and XCN.1 as extension.
<b>Used in Resource Type</b>	DocumentEntry, SubmissionSet

<b>XACML Example</b>	<pre>&lt;Attribute AttributeId="urn:ihe:iti:appc:2016:author-person:id" DataType="urn:hl7-org:v3#II"&gt;   &lt;AttributeValue&gt;     &lt;hl7:InstanceIdentifier extension="11375"       root="1.2.840.113619.6.197"/&gt;   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>
----------------------	--

875 **5.6.2.1.5.1.3 Availability Status**

<b>IHE Document Sharing Metadata Definition</b>	<p>ITI TF-3: 4.2.3.2.2 as "DocumentEntry.availabilityStatus"</p> <p>ITI TF-3: 4.2.3.3.2 as "SubmissionSet.availabilityStatus"</p> <p>ITI TF-3: 4.2.3.4.1 as "Folder.availabilityStatus"</p>
<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:ihe:iti:appc:2016:availability-status
<b>XACML Data Type</b>	http://www.w3.org/2001/XMLSchema#anyURI
<b>XACML Attribute Value Content</b>	"urn:oasis:names:tc:ebxml-regrep:StatusType:Approved" or "urn:oasis:names:tc:ebxml-regrep:StatusType:Deprecated" or any other valid availabilityStatus
<b>Used in Resource Type</b>	DocumentEntry, Folder, SubmissionSet
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId="urn:ihe:iti:appc:2016:availability-status" DataType="http://www.w3.org/2001/XMLSchema#anyURI"&gt;   &lt;AttributeValue&gt;     urn:oasis:names:tc:ebxml-regrep:StatusType:Approved   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

#### 5.6.2.1.5.1.4 Community ID

<b>IHE Document Sharing Metadata Definition</b>	An Object Identifier (OID) that uniquely identifies the community holding the resource in question (e.g., an XDS Affinity Domain holding a document). This is often identical to the homeCommunityId (ITI TF-3: 4.2.3.2.12 as "DocumentEntry.homeCommunityId" and ITI TF-3: 4.2.3.3.6 as "SubmissionSet.homeCommunityId") but may differ from it in complex cross-community scenarios with proxy gateways. For example, a policy writer may use this to restrict access to all data held in a specific community.
<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:ihe:iti:appc:2016:community-id
<b>XACML Data Type</b>	http://www.w3.org/2001/XMLSchema#anyURI
<b>XACML Attribute Value Content</b>	The identifier shall be an Object Identifier (OID), using the urn format ("urn:oid:" followed by the OID)
<b>Used in Resource Type</b>	DocumentEntry, Folder, SubmissionSet
<b>XACML Example</b>	<pre>&lt;Attribute   AttributeId="urn:ihe:iti:appc:2016:community-id"   DataType="http://www.w3.org/2001/XMLSchema#anyURI"&gt;   &lt;AttributeValue&gt;urn:oid:2.999.1.1.12345   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

#### 5.6.2.1.5.1.5 Patient ID

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.2.16 as "DocumentEntry.patientId" ITI TF-3: 4.2.3.3.8 as "SubmissionSet.patientId" ITI TF-3: 4.2.3.4.7 as "Folder.patientId"
<b>XACML Target Section</b>	Resource
<b>XACML Attribute ID</b>	urn:ihe:iti:ser:2016:patient-id
<b>XACML Data Type</b>	urn:hl7-org:v3#II

<b>XACML Attribute Value Content</b>	Use CX.4.2 as root and CX.1 as extension
<b>Used in Resource Type</b>	DocumentEntry, Folder, SubmissionSet
<b>XACML Example</b>	<pre>&lt;Attribute   AttributeId="urn:ihe:iti:ser:2016:patient-id"   DataType="urn:h17-org:v3#II"&gt;   &lt;AttributeValue&gt;     &lt;hl7:InstanceIdentifier extension="6578946"       root="1.3.6.1.4.1.21367.2005.3.7"/&gt;     &lt;/AttributeValue&gt;   &lt;/Attribute&gt;</pre>

#### 5.6.2.1.5.1.6 Source System ID

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.3.9 as "SubmissionSet.sourceId"; in the IHE Document Sharing metadata, the sourceId is only defined for SubmissionSets. To enable source-dependent policies, this attribute is also attached to the XACML representations of DocumentEntries and Folders.
<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:ihe:iti:appc:2016:source-system-id
<b>XACML Data Type</b>	http://www.w3.org/2001/XMLSchema#anyURI
<b>XACML Attribute Value Content</b>	The attribute shall contain the sourceId of the system which originally submitted the object; for a SubmissionSet this is the sourceId, for a DocumentEntry, and for a Folder this is the sourceId of the SubmissionSet used to initially register the object.
<b>Used in Resource Type</b>	DocumentEntry, Folder, SubmissionSet
<b>XACML Example</b>	<pre>&lt;Attribute   AttributeId="urn:ihe:iti:appc:2016:source-system-id"   DataType="http://www.w3.org/2001/XMLSchema#anyURI"&gt;   &lt;AttributeValue&gt;     1.3.6.1.4.1.21367.2005.3.7   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

### 5.6.2.1.5.2 Attribute Definitions – DocumentEntry Resource

880 **5.6.2.1.5.2.1 Class Code**

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.2.3 as "DocumentEntry.classCode"
<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:ihe:iti:appc:2016:document-entry:class-code
<b>XACML Data Type</b>	urn:hl7-org:v3#CV
<b>XACML Attribute Value Content</b>	No restrictions
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId= "urn:ihe:iti:appc:2016:document-entry:class-code" DataType="urn:hl7-org:v3#CV"&gt;   &lt;AttributeValue&gt;     &lt;hl7:CodedValue code="10160-0"       codeSystem="2.16.840.1.113883.6.1"/&gt;   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

### 5.6.2.1.5.2.2 Confidentiality Code

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.2.5 as "DocumentEntry.confidentialityCode"
<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:ihe:iti:appc:2016:confidentiality-code
<b>XACML Data Type</b>	urn:hl7-org:v3#CV
<b>XACML Attribute Value Content</b>	No restrictions

<b>XACML Example</b>	<pre>&lt;Attribute   AttributeId="urn:ihe:iti:appc:2016:confidentiality-code"   DataType="urn:hl7-org:v3#CV"&gt;   &lt;AttributeValue&gt;     &lt;hl7:CodedValue code="N"       codeSystem="2.16.840.1.113883.5.25"/&gt;   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>
----------------------	---

### 5.6.2.1.5.2.3 Creation Time

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.2.6 as "DocumentEntry.creationTime"
<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:ihe:iti:appc:2016:document-entry:creation-time
<b>XACML Data Type</b>	http://www.w3.org/2001/XMLSchema#dateTime
<b>XACML Attribute Value Content</b>	<p>The Content Creator shall transform the creationTime into a valid instance of an XML dateTime (which is based on ISO8601). This may involve adding date or time components, because in Document Sharing metadata the DTM data type allows for partial dates (see ITI TF-3: Table 4.2.3.1.7-2).</p> <p>To transform an incomplete creationTime into a dateTime instance, the Content Creator shall use the smallest instant covered by the partial date. E.g., "200904" would be transformed to "2009-04-01T00:00:00Z".</p> <p>The XACML dateTime shall be expressed as UTC using 'Z' as the timezone indicator. The DTM data type allows only for UTC as the timezone; therefore no further transformation is necessary.</p>
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId=   "urn:ihe:iti:appc:2016:document-entry:creation-time"   DataType="http://www.w3.org/2001/XMLSchema#dateTime"&gt;   &lt;AttributeValue&gt;2004-12-25T21:20:10Z&lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

### 5.6.2.1.5.2.4 Event Code

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.2.8 as "DocumentEntry.eventCodeList"
---	--

<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:ihe:iti:appc:2016:document-entry:event-code
<b>XACML Data Type</b>	urn:hl7-org:v3#CV
<b>XACML Attribute Value Content</b>	No restrictions
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId=   "urn:ihe:iti:appc:2016:document-entry:event-code"   DataType="urn:hl7-org:v3#CV"&gt;   &lt;AttributeValue&gt;     &lt;hl7:CodedValue code="45.23"       codeSystem="2.16.840.1.113883.6.2"/&gt;   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

#### 5.6.2.1.5.2.5 Healthcare Facility Type Code

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.2.11 as "DocumentEntry.healthcareFacilityTypeCode"
<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:ihe:iti:appc:2016:document-entry:healthcare-facility-type-code
<b>XACML Data Type</b>	urn:hl7-org:v3#CV
<b>XACML Attribute Value Content</b>	No restrictions
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId="urn:ihe:iti:appc:2016:document- entry:healthcare-facility-type-code" DataType="urn:hl7-org:v3#CV"&gt;   &lt;AttributeValue&gt;     &lt;hl7:CodedValue code="310400000X"       codeSystem="2.16.840.1.113883.6.101"/&gt;   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

885 **5.6.2.1.5.2.6 Legal Authenticator**

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.2.14 as "DocumentEntry.legalAuthenticator"
<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:ihe:iti:appc:2016:document-entry:legal-authenticator:id
<b>XACML Data Type</b>	urn:hl7-org:v3#II
<b>XACML Attribute Value Content</b>	If XCN.1 is an OID, use XCN.1 as root with no extension. If XCN.1 is not an OID, use XCN.9 as root and XCN.1 as extension.
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId="urn:ihe:iti:appc:2016:document- entry:legal-authenticator:id"   DataType="urn:hl7-org:v3#II"&gt;   &lt;AttributeValue&gt;     &lt;hl7:InstanceIdentifier extension="11375"       root="1.2.840.113619.6.197"/&gt;   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

**5.6.2.1.5.2.7 Practice Setting Code**

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.2.17 as "DocumentEntry.practiceSettingCode"
<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:ihe:iti:appc:2016:document-entry:practice-setting-code
<b>XACML Data Type</b>	urn:hl7-org:v3#CV
<b>XACML Attribute Value Content</b>	No restrictions
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId="urn:ihe:iti:appc:2016:document- entry:practice-setting-code"   DataType="urn:hl7-org:v3#CV"&gt;   &lt;AttributeValue&gt;</pre>



	<pre>                 &lt;hl7:CodedValue code="213ER0200X"                 codeSystem="2.16.840.1.113883.6.101"/&gt;             &lt;/AttributeValue&gt;         &lt;/Attribute&gt;             </pre>
--	--

#### 5.6.2.1.5.2.8 Repository Unique ID

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.2.18 as "DocumentEntry.repositoryUniqueId"
<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:ihe:iti:ser:2016:document-entry:repository-unique-id
<b>XACML Data Type</b>	http://www.w3.org/2001/XMLSchema#anyURI
<b>XACML Attribute Value Content</b>	The identifier shall be an Object Identifier (OID), using the urn format ("urn:oid:" followed by the OID)
<b>XACML Example</b>	<pre>                 &lt;Attribute AttributeId="urn:ihe:iti:ser:2016:document-                 entry:repository-unique-id"                 DataType="http://www.w3.org/2001/XMLSchema#anyURI"&gt;                     &lt;AttributeValue&gt;                         urn:oid:1.3.6.1.4.5                     &lt;/AttributeValue&gt;                 &lt;/Attribute&gt;             </pre>

#### 5.6.2.1.5.2.9 Reference ID List

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.2.28 as "DocumentEntry.referenceIdList"
<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:ihe:iti:appc:2016:document-entry:reference-id
<b>XACML Data Type</b>	urn:hl7-org:v3#II
<b>XACML Attribute Value Content</b>	If CXi.1 is an OID, use CXi.1 as root with no extension. If CXi.1 is not an OID, use CXi.4.2 as root and CXi.1 as extension. CXi.5 is never used.

<b>XACML Example</b>	<pre>&lt;Attribute AttributeId="urn:ihe:iti:appc:2016:document- entry:reference-id"   DataType="urn:hl7-org:v3#II"&gt;   &lt;AttributeValue&gt;     &lt;hl7:InstanceIdentifier extension="2013001"       root="2.999.1"/&gt;   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>
----------------------	---

#### 5.6.2.1.5.2.10 Service Start Time

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.2.19 as "DocumentEntry.serviceStartTime"
<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:ihe:iti:appc:2016:document-entry:service-start-time
<b>XACML Data Type</b>	http://www.w3.org/2001/XMLSchema#dateTime
<b>XACML Attribute Value Content</b>	<p>The Content Creator shall transform the serviceStartTime into a valid instance of an XML dateTime (which is based on ISO8601). This may involve adding date or time components, because in IHE Document Sharing metadata, the DTM data type allows for partial dates (see ITI TF-3: Table 4.2.3.1.7-2).</p> <p>To transform an incomplete serviceStartTime into a dateTime instance, the Content Creator shall use the smallest instant covered by the partial date. E.g., "200904" would be transformed to "2009-04-01T00:00:00Z".</p> <p>The XACML dateTime shall be expressed as UTC using 'Z' as the timezone indicator. The DTM data type allows only for UTC as the timezone, therefore no further transformation is necessary.</p>
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId="urn:ihe:iti:appc:2016:document- entry:service-start-time"   DataType="http://www.w3.org/2001/XMLSchema#dateTime"&gt;   &lt;AttributeValue&gt;2004-12-25T21:20:10Z&lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

890 **5.6.2.1.5.2.11 Service Stop Time**

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.2.20 as "DocumentEntry.serviceStopTime"
---	---

<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:ihe:iti:appc:2016:document-entry:service-stop-time
<b>XACML Data Type</b>	http://www.w3.org/2001/XMLSchema#dateTime
<b>XACML Attribute Value Content</b>	<p>The Content Creator shall transform the serviceStopTime into a valid instance of an XML dateTime (which is based on ISO8601). This may involve adding date or time components, because in IHE Document Sharing metadata, the DTM data type allows for partial dates (see ITI TF-3: Table 4.2.3.1.7-2).</p> <p>To transform an incomplete serviceStopTime into a dateTime instance, the Content Creator shall use the smallest instant covered by the partial date. E.g., "200904" would be transformed to "2009-04-01T00:00:00Z".</p> <p>The XACML dateTime shall be expressed as UTC using 'Z' as the timezone indicator. The DTM data type allows only for UTC as the timezone, therefore no further transformation is necessary.</p>
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId="urn:ihe:iti:appc:2016:document- entry:service-stop-time"   DataType="http://www.w3.org/2001/XMLSchema#dateTime"&gt;   &lt;AttributeValue&gt;2004-12-25T21:20:10Z&lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

#### 5.6.2.1.5.2.12 Source Patient ID

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.2.22 as "DocumentEntry.sourcePatientId"
<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:ihe:iti:appc:2016:document-entry:source-patient-id
<b>XACML Data Type</b>	urn:hl7-org:v3#II

<b>XACML Attribute Value Content</b>	Use CX.4.2 as root and CX.1 as extension. <i>Note: Use of the sourcePatientId attribute of the DocumentEntry has historically been restricted to “audit and checking” purposes. The attribute contains the original local patient ID at the creating facility. It is unlikely to be meaningful or useful outside of this context. Therefore, policy writers need to take this into account.</i>
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId="urn:ihe:iti:appc:2016:document- entry:source-patient-id"   DataType="urn:h17-org:v3#II"&gt;   &lt;AttributeValue&gt;     &lt;h17:InstanceIdentifier extension="j98789"       root="1.2.3.4.343.1"/&gt;     &lt;/AttributeValue&gt;   &lt;/Attribute&gt;</pre>

#### 5.6.2.1.5.2.13 Type Code

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.2.25 as "DocumentEntry.typeCode"
<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:ihe:iti:appc:2016:document-entry:type-code
<b>XACML Data Type</b>	urn:h17-org:v3#CV
<b>XACML Attribute Value Content</b>	No restrictions
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId="urn:ihe:iti:appc:2016:document- entry:type-code"   DataType="urn:h17-org:v3#CV"&gt;   &lt;AttributeValue&gt;     &lt;h17:CodedValue code="57016-8"       codeSystem="2.16.840.1.113883.6.1"/&gt;     &lt;/AttributeValue&gt;   &lt;/Attribute&gt;</pre>

#### 5.6.2.1.5.2.14 Document Unique ID

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.2.26 as "DocumentEntry.uniqueId"
---	--

<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:oasis:names:tc:xacml:1.0:resource:resource-id
<b>XACML Data Type</b>	http://www.w3.org/2001/XMLSchema#string
<b>XACML Attribute Value Content</b>	No restrictions
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId=   "urn:oasis:names:tc:xacml:1.0:resource:resource-id"   DataType="http://www.w3.org/2001/XMLSchema#string"&gt;   &lt;AttributeValue&gt;     1.2.3.4.5.6.78901.2345.6.7^123456   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

#### 5.6.2.1.5.2.15 Related Folder Unique ID

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.4.9 as "Folder.uniqueId"
<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:ihe:iti:appc:2016:document-entry:related-folder:id
<b>XACML Data Type</b>	http://www.w3.org/2001/XMLSchema#anyURI
<b>XACML Attribute Value Content</b>	<p>The Content Creator may include the Folder.uniqueId for each unique folder that it requires to be associated with the document entry, i.e., folders that are associated via the hasMember association and where the folder availabilityStatus is "Approved".</p> <p>Note that this attribute is used to write policies regarding access to document entries. When writing policies regarding access to folders that include the Folder.uniqueId, refer to Section 5.6.2.1.5.3.3.</p>

<b>XACML Example</b>	<pre>&lt;Attribute AttributeId="urn:ihe:iti:appc:2016:document- entry:related-folder:id"   DataType="http://www.w3.org/2001/XMLSchema#anyURI"&gt;   &lt;AttributeValue&gt;     urn:oid:1.3.6.1.4.1.21367.2005.3.7.3670984664   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>
----------------------	---

895 **5.6.2.1.5.2.16 Related Folder Code**

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.4.2 as "Folder.codeList"
<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:ihe:iti:appc:2016:document-entry:related-folder:code
<b>XACML Data Type</b>	urn:hl7-org:v3#CV
<b>XACML Attribute Value Content</b>	<p>The Content Creator may include a Folder.codeList entry to characterize a folder that it requires to be currently associated with the document entry, i.e., folders that are associated via the hasMember association and where the folder availabilityStatus is "Approved".</p> <p>Note that this attribute is used to write policies regarding access to document entries. When writing policies regarding access to folders that have a specific Folder.codeList entry, refer to Section 5.6.2.1.5.3.1.</p>
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId="urn:ihe:iti:appc:2016:document- entry:related-folder:code"   DataType="urn:hl7-org:v3#CV"&gt;   &lt;AttributeValue&gt;     &lt;hl7:CodedValue code="EMER"       codeSystem="2.16.840.1.113883.1.11.13955"/&gt;   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

**5.6.2.1.5.2.17 Resource Type**

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.2 as "DocumentEntry"
<b>XACML Target Section</b>	resource

<b>XACML Attribute ID</b>	urn:ihe:iti:appc:2016:resource-type
<b>XACML Data Type</b>	http://www.w3.org/2001/XMLSchema#anyURI
<b>XACML Attribute Value Content</b>	for document entries the value of the attribute shall be "urn:ihe:iti:appc:2016:document-entry"
<b>XACML Example</b>	<pre>&lt;Attribute   AttributeId="urn:ihe:iti:appc:2016:resource-type"   DataType="http://www.w3.org/2001/XMLSchema#anyURI"&gt;   &lt;AttributeValue&gt;     urn:ihe:iti:appc:2016:document-entry   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

### 5.6.2.1.5.3 Attribute Definitions - Folder Resource

#### 5.6.2.1.5.3.1 Code

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.4.2 as "Folder.codeList"
<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:ihe:iti:appc:2016:folder:code
<b>XACML Data Type</b>	urn:hl7-org:v3#CV
<b>XACML Attribute Value Content</b>	No restrictions
<b>XACML Example</b>	<pre>&lt;Attribute   AttributeId="urn:ihe:iti:appc:2016:folder:code"   DataType="urn:hl7-org:v3#CV"&gt;   &lt;AttributeValue&gt;     &lt;hl7:CodedValue code="EMER"       codeSystem="2.16.840.1.113883.1.11.13955"/&gt;   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

### 5.6.2.1.5.3.2 Last Update Time

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.4.6 as "Folder.lastUpdateTime"
<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:ihe:iti:appc:2016:folder:last-update-time
<b>XACML Data Type</b>	http://www.w3.org/2001/XMLSchema#dateTime
<b>XACML Attribute Value Content</b>	The Content Creator shall transform the lastUpdateTime into a valid instance of an XML dateTime (which is based on ISO8601). This does not involve adding date or time components, because the last update time is set automatically by the Document Registry. The XACML dateTime shall be expressed as UTC using 'Z' as the timezone indicator. The DTM data type allows only for UTC as the timezone, therefore no further transformation is necessary.
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId="urn:ihe:iti:appc:2016:folder:last-update-time"   DataType="http://www.w3.org/2001/XMLSchema#dateTime"&gt;   &lt;AttributeValue&gt;2004-12-25T21:20:10Z&lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

900

### 5.6.2.1.5.3.3 Folder UniqueId

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.4.9 as "Folder.uniqueId"
<b>XACML Target Section</b>	Resource
<b>XACML Attribute ID</b>	urn:oasis:names:tc:xacml:1.0:resource:resource-id
<b>XACML Data Type</b>	http://www.w3.org/2001/XMLSchema#string
<b>XACML Attribute Value Content</b>	No restrictions
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId=   "urn:oasis:names:tc:xacml:1.0:resource:resource-id"   DataType="http://www.w3.org/2001/XMLSchema#string"&gt;</pre>



	<pre>&lt;AttributeValue&gt;   1.3.6.1.4.1.21367.2005.3.7.3670984664 &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>
--	--

#### 5.6.2.1.5.3.4 Resource Type

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.4 as “Folder”
<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:ihe:iti:appc:2016:resource-type
<b>XACML Data Type</b>	http://www.w3.org/2001/XMLSchema#anyURI
<b>XACML Attribute Value Content</b>	for folders the value of the attribute shall be "urn:ihe:iti:appc:2016:folder"
<b>XACML Example</b>	<pre>&lt;Attribute   AttributeId="urn:ihe:iti:appc:2016:resource-type"   DataType="http://www.w3.org/2001/XMLSchema#anyURI"&gt;   &lt;AttributeValue&gt;     urn:ihe:iti:appc:2016:folder   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

#### 5.6.2.1.5.4 Attribute Definitions - SubmissionSet Resource

##### 5.6.2.1.5.4.1 Content Type

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.3.4 as "SubmissionSet.contentTypeCode"
<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:ihe:iti:appc:2016:submission-set:content-type
<b>XACML Data Type</b>	urn:h17-org:v3#CV

<b>XACML Attribute Value Content</b>	No restrictions
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId=   "urn:ihe:iti:appc:2016:submission-set:content-type"   DataType="urn:hl7-org:v3#CV"&gt;   &lt;AttributeValue&gt;     &lt;hl7:CodedValue code="47046-8"       codeSystem="2.16.840.1.113883.6.1"/&gt;   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

905 **5.6.2.1.5.4.2 Intended Recipient Id**

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.3.7 as "SubmissionSet.intendedRecipient"
<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:ihe:iti:appc:2016:submission-set:intended-recipient:id
<b>XACML Data Type</b>	urn:hl7-org:v3#II
<b>XACML Attribute Value Content</b>	<p>For persons, if XCN.1 is an OID, use XCN.1 as root with no extension. If XCN.1 is not an OID, use XCN.9 as root and XCN.1 as extension.</p> <p>For organizations, if XON.10 is an OID, use XON.10 as a root with no extension. If XON.10 is not an OID, use XON.6.2 as root and XON.10 as extension.</p>
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId="urn:ihe:iti:appc:2016:submission- set:intended-recipient:id"   DataType="urn:hl7-org:v3#II"&gt;   &lt;AttributeValue&gt;     &lt;hl7:InstanceIdentifier extension="11375"       root="2.999.1"/&gt;   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

**5.6.2.1.5.4.3 Intended Recipient Email**

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.3.7 as "SubmissionSet.intendedRecipient"
---	--

<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:ihe:iti:appc:2016:submission-set:intended-recipient:email
<b>XACML Data Type</b>	urn:oasis:names:tc:xacml:1.0:data-type:rfc822Name
<b>XACML Attribute Value Content</b>	For telecommunications, XTN.3 has the value “Internet”. Use the email address in XTN.4 as the value of the attribute.
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId="urn:ihe:iti:appc:2016:submission-set:intended-recipient:email"   DataType=     "urn:oasis:names:tc:xacml:1.0:data-type:rfc822Name"&gt;   &lt;AttributeValue&gt;     john.doe@healthcare.example.org   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

#### 5.6.2.1.5.4.4 Submission Time

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.3.10 as "SubmissionSet.submissionTime"
<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:ihe:iti:appc:2016:submission-set:submission-time
<b>XACML Data Type</b>	http://www.w3.org/2001/XMLSchema#dateTime

<b>XACML Attribute Value Content</b>	<p>The Content Creator shall transform the submissionTime into a valid instance of an XML dateTime (which is based on ISO8601). This may involve adding date or time components, because in IHE Document Sharing metadata, the DTM data type allows for partial dates (see ITI TF-3: Table 4.2.3.1.7-2).</p> <p>To transform an incomplete submissionTime into a dateTime instance, the Content Creator shall use the smallest instant covered by the partial date. E.g., "200904" would be transformed to "2009-04-01T00:00:00Z".</p> <p>The XACML dateTime shall be expressed as UTC using ,Z' as the timezone indicator. The DTM data type allows only for UTC as the timezone, therefore no further transformation is necessary.</p>
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId=   "urn:ihe:iti:appc:2016:submission-set:submission-time"   DataType="http://www.w3.org/2001/XMLSchema#dateTime"&gt;   &lt;AttributeValue&gt;     2004-12-25T21:20:10Z   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

#### 5.6.2.1.5.4.5 Submission Set Unique ID

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.3.12 as "SubmissionSet.uniqueId"
<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:oasis:names:tc:xacml:1.0:resource:resource-id
<b>XACML Data Type</b>	http://www.w3.org/2001/XMLSchema#string
<b>XACML Attribute Value Content</b>	No restrictions
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId=   "urn:oasis:names:tc:xacml:1.0:resource:resource-id"   DataType="http://www.w3.org/2001/XMLSchema#string"&gt;   &lt;AttributeValue&gt;     1.2.3.4.5   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

#### 5.6.2.1.5.4.6 Resource Type

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-3: 4.2.3.3 as “SubmissionSet”
<b>XACML Target Section</b>	resource
<b>XACML Attribute ID</b>	urn:ihe:iti:appc:2016:resource-type
<b>XACML Data Type</b>	http://www.w3.org/2001/XMLSchema#anyURI
<b>XACML Attribute Value Content</b>	for submission sets the value of the attribute shall be "urn:ihe:iti:appc:2016:submission-set"
<b>XACML Example</b>	<pre>&lt;Attribute   AttributeId="urn:ihe:iti:appc:2016:resource-type"   DataType="http://www.w3.org/2001/XMLSchema#anyURI"&gt;   &lt;AttributeValue&gt;     urn:ihe:iti:appc:2016:submission-set   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

910

#### 5.6.2.1.6 Attribute Definitions – Action

##### 5.6.2.1.6.1 Action URIs

915 The Content Creator of a Privacy Consent Document shall use the action URIs in the following table when referring to the transactions in IHE Document Sharing profiles. The action URIs are used in attributes with attribute ID urn:oasis:names:tc:xacml:1.0:action:action-id and data type http://www.w3.org/2001/XMLSchema#anyURI.

Transaction	Action URI
ITI-18 Response	urn:ihe:iti:2007:RegistryStoredQueryResponse
ITI-38 Response	urn:ihe:iti:2007:CrossGatewayQueryResponse
ITI-39 Response	urn:ihe:iti:2007:CrossGatewayRetrieveResponse
ITI-41	urn:ihe:iti:2007:RegisterDocumentSet-b
ITI-42	urn:ihe:iti:2007:ProvideAndRegisterDocumentSet-b
ITI-43 Response	urn:ihe:iti:2007:RetrieveDocumentSetResponse
ITI-51 Response	urn:ihe:iti:2009:MultiPatientStoredQueryResponse

Transaction	Action URI
ITI-61	urn:ihe:iti:2010:RegisterOnDemandDocumentEntry
RAD-69 Response	urn:ihe:rad:2009:RetrieveImagingDocumentSetResponse
RAD-75 Response	urn:ihe:rad:2011:CrossGatewayRetrieveImagingDocumentSetResponse

#### 5.6.2.1.6.2 Additional Action Attribute – Query ID

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-2a: 3.18.4.1.2.3.2 Parameter Query ID
<b>XACML Target Section</b>	action
<b>XACML Attribute ID</b>	urn:ihe:iti:2016:RegistryStoredQuery:queryId
<b>XACML Data Type</b>	http://www.w3.org/2001/XMLSchema#anyURI
<b>XACML Attribute Value Content</b>	Shall contain one of the stored query IDs defined in ITI TF-2a: 3.18.4.1.2.4 or in ITI TF-2b: 3.51.4.1.2.2.
<b>Attribute ID used in</b>	Attributes with action ID urn:ihe:iti:2007:RegistryStoredQueryResponse
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId="urn:ihe:iti:2016:RegistryStoredQuery:queryId" DataType="http://www.w3.org/2001/XMLSchema#anyURI"&gt;   &lt;AttributeValue&gt;     urn:uuid:14d4debf-8f97-4251-9a74-a90016b0af0d   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

#### 5.6.2.1.6.3 Additional Action Attribute – Return Type

<b>IHE Document Sharing Metadata Definition</b>	ITI TF-2a: 3.18.4.1.2.3.1 Parameter returnType
<b>XACML Target Section</b>	action
<b>XACML Attribute ID</b>	urn:ihe:iti:2016:RegistryStoredQuery:returnType

<b>XACML Data Type</b>	<code>http://www.w3.org/2001/XMLSchema#anyURI</code>
<b>XACML Attribute Value Content</b>	Shall contain either <code>urn:ihe:iti:xds-b:2016:leaf-class</code> or <code>urn:ihe:iti:xds-b:2016:object-ref</code>
<b>Attribute ID used in</b>	Attributes with action ID <code>urn:ihe:iti:2007:RegistryStoredQueryResponse</code>
<b>XACML Example</b>	<pre>&lt;Attribute AttributeId=   "urn:ihe:iti:2016:RegistryStoredQuery:returnType"   DataType="http://www.w3.org/2001/XMLSchema#anyURI"&gt;   &lt;AttributeValue&gt;     urn:ihe:iti:xds-b:2016:leaf-class   &lt;/AttributeValue&gt; &lt;/Attribute&gt;</pre>

920 **5.6.2.1.7 Attribute Definitions – Environment**

No additional constraints.

**5.6.2.2 Document Sharing Metadata**

925 When Privacy Consent Documents are shared using IHE Document Sharing profiles, their metadata follows the requirements specified in Section 4.2.3. Only the following attributes have special rules.

**5.6.2.2.1 XDS DocumentEntry Metadata**

**5.6.2.2.1.1 XDSDocumentEntry.typeCode**

The LOINC code for these documents is “57016-8” “Privacy Policy Acknowledgement Document” and the codeSystem is 2.16.840.1.113883.6.1.

930 **5.6.2.2.1.2 XDSDocumentEntry.eventCodeList**

A Privacy Consent Document can reference previously defined policies. This allows the Patient Privacy Policy Domain to define foundational policies that are applied to specific individuals and situations by the Privacy Consent Document.

935 The `PolicySetIdReference` or `PolicyIdReference` values not defined in the document shall be used as the code, with a coding scheme defined by the XDS Affinity Domain.

**5.6.2.2.1.3 XDSDocumentEntry.formatCode**

The `XDSDocumentEntry` format code for this content shall be `urn:ihe:iti:appc:2016:consent`. The `formatCode` codeSystem shall be 1.3.6.1.4.1.19376.1.2.3.

940 **5.6.2.2.1.4 XSDDocumentEntry.uniqueId**

The Root Policy Set ID in the Privacy Consent Document shall be used as the XSDDocumentEntry.uniqueId.

**5.6.2.2.1.5 XSDDocumentEntry.title**

945 The title should reflect the human readable representation in the /PolicySet/Description element.

**5.6.2.2.1.6 XSDDocumentEntry.serviceStartTime**

950 The serviceStartTime shall be empty or contain the earliest point in time that parts of the Privacy Consent Document are relevant. If the serviceStartTime is empty, it is equivalent to the earliest point in time. The structured policy may contain additional date and time constraints that are not reflected in the serviceStartTime.

**5.6.2.2.1.7 XSDDocumentEntry.serviceStopTime**

955 The serviceStopTime shall be empty or contain the latest point in time that parts of the Privacy Consent Document are relevant. If the serviceStopTime is empty, it is equivalent to the latest point in time. The structured policy may contain additional date and time constraints that are not reflected in the serviceStopTime.

**5.6.2.2.1.8 XSDDocumentEntry.referenceIdList**

A Privacy Consent Document can reference previously defined policies. This allows the Patient Privacy Policy Domain to define foundational policies that are applied to specific individuals and situations by the Privacy Consent Document.

960 In an XDS Affinity Domain that supports the referenceIdList, PolicySetIdReference or PolicyIdReference values not defined in the document shall be included in the referenceIdList.

**5.6.2.2.2 XDS SubmissionSet Metadata**

No additional constraints.

**5.6.2.2.3 XDS Folder Metadata**

965 No additional constraints.



Update ITI TF Vol 3: Table 4.2.3.1.7-2:

**Table 4.2.3.1.7-2: Data Types (previously Table 4.1-3)**

Data Type	Source Standard	Encoding Specification
...		
CXi	HL7 V2 Identifier	<p>This is an identifier of a reference object, distinct from the use of CX for Patient Identifiers. HL7 Identifier type CX consists of several components.</p> <p>...</p> <p><b><u>urn:ihe:iti:xdw:2013:workflowId</u></b></p> <p>This code shall be used when the identifier is an XDW workflow identifier. The workflow identifier shall be an OID. Only the CXi.1 and CXi.5 component shall be present:</p> <p>For example, if the workflow identifier is “2.16.840.1” the CXi value is:  <code>2.16.840.1^^^^urn:ihe:iti:xdw:2013:workflowInstanceId</code></p> <p><b><u>urn:ihe:iti:appc:2016:policyId</u></b></p> <p><b><u>This code shall be used when the identifier is a privacy policy identifier.</u></b></p> <p><b><u>For example:</u></b>  <code><u>2.999.1.3.4.5.19812371516^^^^urn:ihe:iti:xds:2016:policyId</u></code></p> <p>...</p>
...		

970

### Volume 3 Namespace Additions

*Add the following terms to the IHE Namespace:*

URN	Reference to Description
urn:ihe:iti:appc:2016:author-institution:id	ITI TF-3: 4.2.3.1.4.1 authorInstitution (XON.6/XON.10)
urn:ihe:iti:appc:2016:author-person:id	ITI TF-3: 4.2.3.1.4.2 authorPerson (XCN.1/XCN.9)
urn:ihe:iti:appc:2016:availability-status	ITI TF-3: 4.2.3.2.2 DocumentEntry.availabilityStatus or ITI TF-3: 4.2.3.3.2 SubmissionSet.availabilityStatus or ITI TF-3: 4.2.3.4.1 Folder.availabilityStatus
urn:ihe:iti:appc:2016:community-id	An Object Identifier (OID) which uniquely identifies the community holding the resource in question
urn:ihe:iti:appc:2016:source-system-id	ITI TF-3: 4.2.3.3.9 SubmissionSet.sourceId
urn:ihe:iti:appc:2016:document-entry:class-code	ITI TF-3: 4.2.3.2.3 DocumentEntry.classCode
urn:ihe:iti:appc:2016:confidentiality-code	ITI TF-3: 4.2.3.2.5 DocumentEntry.confidentialityCode
urn:ihe:iti:appc:2016:document-entry:creation-time	ITI TF-3: 4.2.3.2.6 DocumentEntry.creationTime
urn:ihe:iti:appc:2016:document-entry:event-code	ITI TF-3: 4.2.3.2.8 DocumentEntry.eventCodeList
urn:ihe:iti:appc:2016:document-entry:healthcare-facility-type-code	ITI TF-3: 4.2.3.2.11 DocumentEntry.healthcareFacilityTypeCode
urn:ihe:iti:appc:2016:document-entry:legal-authenticator:id	ITI TF-3: 4.2.3.2.14 DocumentEntry.legalAuthenticator
urn:ihe:iti:appc:2016:document-entry:reference-id	ITI TF-3: 4.2.3.2.28 DocumentEntry.referenceIdList
urn:ihe:iti:appc:2016:document-entry:practice-setting-code	ITI TF-3: 4.2.3.2.17 DocumentEntry.practiceSettingCode
urn:ihe:iti:appc:2016:document-entry:service-start-time	ITI TF-3: 4.2.3.2.19 DocumentEntry.serviceStartTime
urn:ihe:iti:appc:2016:document-entry:service-stop-time	ITI TF-3: 4.2.3.2.20 DocumentEntry.serviceStopTime
urn:ihe:iti:appc:2016:document-entry:source-patient-id	ITI TF-3: 4.2.3.2.22 DocumentEntry.sourcePatientId
urn:ihe:iti:appc:2016:document-entry:type-code	ITI TF-3: 4.2.3.2.25 DocumentEntry.typeCode
urn:ihe:iti:appc:2016:document-entry:related-folder:id	ITI TF-3: 4.2.3.4.9 Folder.uniqueId linked to a DocumentEntry through an active association
urn:ihe:iti:appc:2016:document-entry:related-folder:code	ITI TF-3: 4.2.3.4.2 Folder.codeList linked to a DocumentEntry through an active association

IHE IT Infrastructure Technical Framework Supplement – Advanced Patient Privacy Consents (APPC)

URN	Reference to Description
urn:ihe:iti:appc:2016:resource-type	Attribute to distinguish between different types of XACML resource, e.g., DocumentEntry, Folder, SubmissionSet
urn:ihe:iti:appc:2016:folder:code	ITI TF-3: 4.2.3.4.2 Folder.codeList
urn:ihe:iti:appc:2016:folder:last-update-time	ITI TF-3: 4.2.3.4.6 Folder.lastUpdateTime
urn:ihe:iti:appc:2016:submission-set:content-type	ITI TF-3: 4.2.3.3.4 SubmissionSet.contentTypeCode
urn:ihe:iti:appc:2016:submission-set:submission-time	ITI TF-3: 4.2.3.3.10 SubmissionSet.submissionTime
urn:ihe:iti:appc:2016:submission-set:intended-recipient:id	ITI TF-3: 4.2.3.37 SubmissionSet.intendedRecipient (XCN or XON)
urn:ihe:iti:appc:2016:submission-set:intended-recipient:email	ITI TF-3: 4.2.3.37 SubmissionSet.intendedRecipient (XTN)

975

Profile	Format Code	Media Type	Template ID
Advanced Patient Privacy Consents (APPC)	urn:ihe:iti:appc:2016:consent	text/xml	not applicable